JBL AC118S Specs

Active or Passive	Passive
Frequency Response ± 3dB	40 Hz to 250 Hz
Frequency Range	-10 dB: 32 to 250 Hz
Power Capacity	Long-Term System: 450 W/900 W/1800 W (Continuous/Program/Peak) System Power Rating (AES): 600 W (2400 W peak), 2 hours
Maximum Sound Pressure Level (SPL)	3.2' (1 m): 122 dB (128 dB peak)
Nominal Sensitivity	1 W @ 3.2' / 1 m: 95 dB
Impedance	8 Ohms
Crossover	Not specified by the manufacturer
Low Frequency Driver	1 x 18" (457 mm) driver (P/N: 5021800), with 3" (75 mm) voice-coil
Enclosure Material	3/4" (18 mm) multi-ply hardwood plywood Grille: Powder coated, 0.05" (1.5 mm) perforated steel, with acoustically transparent black foam backing
Input Connections	Dual Neutrik NL4MP connectors plus

covered	harriar	trin	terminals
Covered	Dalliel	uip	(CIIIIIIais

Mounting	12 x M10 threaded suspension points
Dimensions	21.5 x 22 x 28.3" (548 x 561 x 720 mm)
Weight	71.2 lb (32.3 kg)

Packaging Info

Package Weight	93 lb
Box Dimensions (LxWxH)	30 x 25 x 24"