

# JBL AL7115 Specs

Frequency Range	40 Hz to 4.2 kHz (-10 dB)
Frequency Response &#177; 3dB	47 Hz to 3.0 kHz
Transducer Power Rating	1000 W (4000 W peak), 2 hours (AES)
Long-Term System Power Rating	600 W (2400 W peak), 100 hours (IEC)
Maximum SPL	50 Hz to 125 Hz: 127 dB-SPL cont. avg. (133 dB peak) 125 Hz to 800 Hz: 126 dB-SPL cont. avg. (132 dB peak)
System Sensitivity	@(dB SPL, 1W @ 1m) 50 Hz to 125 Hz: 97 dB 125 Hz to 800 Hz: 97 dB
Nominal Impedance	8 ohms
Low Frequency Driver	1 x JBL 2265H 15" (380 mm) Differential Drive driver with 3" (75 mm) dual voice coil
Enclosure	Trapezoidal with 15 degree side angles 5/8" (16 mm) exterior grade 11-ply Finnish birch plywood
Suspension Support	13 points (3 top, 3 bottom, 2 each side, 3 rear), M10 threaded hardware

---

Finish	Black DuraFlex™ finish
Grille	Powder coated 14 gauge perforated steel, with acoustically transparent black foam backing
Input Connectors	NL4 Neutrik Speakon and CE-compliant covered barrier strip terminals (Barrier terminals accept up to 5.2 sq mm (10 AWG) wire or max width 0.375" (9 mm) spade lugs Speakon in parallel with barrier strip for loop-through
Environment Requirements	Mil-Std 810 IP-x3 per IEC529
Dimensions (H x W x D)	21.6 x 22.1 x 25.9" (548 x 561 x 657 mm)(vertical cabinet orientation)
Weight	57 lb (25.9 kg)

---

## Packaging Info

---

Package Weight	68 lb
Box Dimensions (LxWxH)	29.5 x 26 x 23.5"

---