# JBL C64P/T Specs

## Speaker

Active or Passive	Passive
Speaker Configuration	Full-Range
Power Handling	For 100 Hours: 40 W RMS 160 W Peak For 2 Hours: 100 W Program 50 W RMS 200 W Peak
Constant Voltage / Transformer Taps	<b>100 V:</b> 30 / 15 / 7.5 W <b>70 V:</b> 30 / 15 / 7.5 / 3.7 W
Impedance	8 Ohms

#### Drivers

Full-Range Driver	4" / 101.6 mm Polypropylene-Coated Paper
Full-Range Voice Coil	0.8" / 20 mm

#### Performance

Frequency Range	85 Hz to 14 kHz ±3 dB
Frequency Response	65 Hz to 15 kHz -10 dB
Maximum SPL	105 dB (Continuous) 111 dB (Peak)
Sensitivity	88 dB
Coverage Angle	120° H x 120° V <b>③</b>
Directivity	6.2 (Directivity/Q Factor) 7.3 dB (Directivity Index)
Maximum Input Voltage	18.2 V RMS 36.4 V Peak <sup>©</sup>
Transformer Insertion Loss	0.94 dB at 3.7 W 0.89 dB at 7.5 W 0.83 dB at 15 W 0.94 dB at 30 W

### Connectivity

I/O Connectors	2 x Euroblock 2-Pin Screw Terminal©
Maximum Wire Gauge	12 AWG / 2.5 mm

### Environmental

Certifications

UL, as per Manufacturer

IP Rating	IP44

# Physical

Color	Black
Mounting	Suspension
Construction Material	High-Impact Polystyrene, Metal Grille
Dimensions	9.3 x 10.2" / 234 x 259 mm <sup>©</sup>
Weight	5.2 lb / 2.4 kg

## Packaging Info

Package Weight	13.5 lb
Box Dimensions (LxWxH)	20.8 x 13.2 x 10.8"