

Specifications

System Type	Self Powered 15", two-way, bass-reflex
Maximum SPL	Normal: 137 dB Boost: 137 dB
Frequency Range (-10 dB)	Main: 42.9 Hz - 19.5 kHz Monitor: 43.6 Hz - 19.3 kHz
Frequency Response (± 3 dB)	Main: 58.1 Hz - 17.2 kHz Monitor: 60.7 Hz - 16.7 kHz
Input Connectors	2 x Balanced XLR / 1/4 inch input, 2 x unbalanced RCA input
Input Impedance	20K Ohms (balanced), 10K Ohms (unbalanced)
Signal Indicators	Limit: Yellow LED indicates peak output has been reached and dsp limiter is acting Signal: Green LED indicates signal present Power: Blue indicates system has power and ready to pass audio
EQ	User selectable presets for Main or Monitor position, Advanced EQ settings available using Wi-Fi and PRX Connect application
Dynamic Control (Input)	dbx Type IV™ limiter circuit
Crossover Frequency	2 kHz
Design	Highly efficient Class-D amplifier
Power Rating	1500W (750W x 2)
AC power input	100V - 240V ~ 50/60 Hz
LF Driver	1 x JBL 275G (15 in) woofer
HF Driver	1 x JBL 2408H-2 37.5 mm (1.5 in) annular polymer diaphragm, neodymium compression driver
Coverage Pattern	90° x 50° nominal
Directivity Index (DI)	10.2 dB

Directivity Factor (Q)	10.4
Enclosure	Asymmetrical, 18 mm, plywood
Suspension / Mounting	Dual 36 mm pole socket, 12 x M10 Suspension Points
Transport	1 x injection molded handle with backing cup
Finish	Obsidian DuraFlex™ finish
Grille	Powder coated, Obsidian, 16 gauge perforated steel with acoustical transparent black cloth backing.
Dimensions (H x W x D)	701 mm x 446 mm x 359 mm (27.6 in x 17.5 in x 14.1 in)
Net Weight	20.86 kg (46.0 lb)
Gross Weight	26.3 kg (58.0 lb)