

---

<b>Printing method</b>	9-pin serial impact dot matrix printer
------------------------	--

<b>Technology</b>	Serial Impact Dot Matrix Printer
-------------------	----------------------------------

---

## Fonts and styles

<b>Print speed</b>	311/233 cps
--------------------	-------------

<b>Receipt column capacity</b>	Paper width 69.5 mm, 30/40
--------------------------------	----------------------------

<b>Supporting column capacity</b>	66 cps / 88 cps
-----------------------------------	-----------------

<b>Letter size</b>	1.6mm (W) x 3.1mm (H) / 1.3mm (W) x 3.1mm (H)
--------------------	---

<b>Character register</b>	95 alphanumeric, 32 international, 128 × 9 graphic
---------------------------	--

<b>Characters per inch</b>	16.7 cpi / 12.5 cpi
----------------------------	---------------------

---

## Paper

<b>Paper types</b>	Journal, receipt, receipt
--------------------	---------------------------

<b>Proof copy capacity</b>	four copies plus one original
----------------------------	-------------------------------

<b>Paper format, roll paper</b>	69.50 ± 0.50 (width) mm x diam. 83.00 mm
---------------------------------	--

<b>Paper format, proof</b>	70 - 210 mm (width) x 70 - 297 mm (height)
----------------------------	--

---

## Interfaces

<b>Interfaces</b>	Drawer opening, Client display, USB 2.0 type B
-------------------	--

---

## Switched on

<b>Power supply</b>	PS-180 (option)
<b>Energy consumption</b>	Standby: 0.3 A, Medium: 1.8 A
<b>Service voltage</b>	24 V

---

## general

<b>Product dimensions</b>	251 x 298 x 195 mm (Width x Depth x Height)
<b>Weight</b>	5.6 kg
<b>Color</b>	Epson Cool White
<b>Installation</b>	Horizontal
<b>Interface connectors</b>	DKD function (2 drivers), Customer display port
<b>Noise level</b>	Operation: 63 dB (A)
<b>Air humidity</b>	Operation 30% - 80%, storage 30% - 90%
<b>Temperature</b>	Operation 5 ° C - 40 ° C, storage -10 ° C - 50 ° C

---

## Reliability

<b>Reliability</b>	18,000,000 MCBF (lines), 180,000 MTBF (hours)
<b>Printer life</b>	7,500,000 lines
<b>Proof Printer Ribbon Life</b>	4,500,000 characters
<b>Print head life</b>	150 million character (s)

---

## According to standards

<b>EMC standards</b>	CE mark
<b>Safety standards</b>	TÜV

---

## Other functions

<b>Cutting unit</b>	Partial cut
<b>Factory options</b>	MICR device
<b>Sensors</b>	Cover Open Sensor, Receipt Eject Sensor, End of Journal Near Sensor, End of Receipt Sensor Near, Newspaper Sensor, Receipt Sensor, Receipt Insertion Sensor

---

## What is in the box

<b>It includes</b>	Equipment, Roll Paper Tension Coil, Connection Button Cover, Ink Ribbon, Roll Paper, User Manual
--------------------	--

---

## Others

<b>Warranty</b>	12 months Workshop repair
-----------------	---------------------------

---