

Specifications

Print type

Print method	Thermal line printing
Technology	Thermal Line

Fonts & Styles

Print Speed	200 mm/sec
Print Speed receipt	200 mm/sec
Printing Font	ANK
Printing Font Receipt	ANK
Column capacity receipt	Paper width 80 mm, 48 / 57
Character set	95 Alphanumeric, 18 set International, 128 x 43 Graphic
Dot density	203 dpi x 203 dpi
Printing Characters	Text (incl. Euro symbol), Graphics, Barcode

Paper

Paper Types	Receipt
Paper size	58 mm - 80 mm (Width)
Paper size roll paper	57.50 ± 0.50 (W) mm x dia 18.00 mm, 57.50 ± 0.50 (W) mm x dia 83.00 mm, 79.50 ± 0.50 (W) mm x dia 18.00 mm, 79.50 ± 0.50 (W) mm x dia 83.00 mm

Interfaces

Interfaces	Ethernet interface (100 Base-TX / 10 Base-T), Bluetooth, USB 2.0 Type B, USB 2.0 Type A, Drawer kick-out
------------	--

data buffer

Data Buffer	12 kB
-------------	-------

Power

Power Supply	AC adapter, C, UK AC cable
--------------	----------------------------

General

Product dimensions	127 x 127 x 127 mm (Width x Depth x Height)
Product weight	1.3 kg
Colour	White
Installation	horizontally, vertically, wall hanging
Interface connectors	D.K.D. function
Noise Level	Operation: 55 dB (A)
Humidity	Operation 10% - 90%, Storage 10% - 90%
Temperature	Operation 5° C - 45° C, Storage -20° C - 60° C

Reliability

Reliability	60,000,000 MCBF (Lines), 360,000 MTBF (Hours)
Auto Cutter Life	1,500,000 Cuts
Printer Life	15,000,000 Lines
Print Head Life	100 km - 100,000,000 pulses

Other Features

NFC	Near Field Communication available
Cutter	Partial Cut
Sensors	Paper End Sensor, Paper sensor

What's in the box

What's in the box	AC adapter, C1, AC cable, Cable fixation saddle, Main unit, Paper spacer, Power switch cover, Roll paper, Setup guide, Warranty document
-------------------	--

Other

Warranty	24 months Carry in
----------	--------------------