

# Specifications

---

## Print type

Print method	Thermal line printing
Technology	Thermal Line

## Fonts & Styles

Print Speed	200 mm/sec
Print Speed receipt	200 mm/sec
Printing Font	ANK
Printing Font Receipt	ANK
Column capacity receipt	Paper width 80 mm, 48 / 57
Character set	95 Alphanumeric, 18 set International, 128 x 43 Graphic
Dot density	203 dpi x 203 dpi
Printing Characters	Text (incl. Euro symbol), Graphics, Barcode

## Paper

Paper Types	Receipt
Paper size	58 mm - 80 mm (Width)
Paper size roll paper	57.50 ± 0.50 (W) mm x dia 18.00 mm, 57.50 ± 0.50 (W) mm x dia 83.00 mm, 79.50 ± 0.50 (W) mm x dia 18.00 mm, 79.50 ± 0.50 (W) mm x dia 83.00 mm

## Interfaces

Interfaces	Ethernet interface (100 Base-TX / 10 Base-T), Drawer kick-out, USB 2.0 Type A
------------	---

## data buffer

Data Buffer	12 kB
-------------	-------

## Power

Power Supply	AC adapter, C, EURO AC cable
--------------	------------------------------

## General

Product dimensions	127 x 127 x 127 mm (Width x Depth x Height)
Product weight	1.3 kg
Colour	Black
Installation	horizontally, vertically, wall hanging
Interface connectors	D.K.D. function
Noise Level	Operation: 55 dB (A)
Humidity	Operation 10% - 90%, Storage 10% - 90%
Temperature	Operation 5° C - 45° C, Storage -20° C - 60° C

## Reliability

Reliability	60,000,000 MCBF (Lines), 360,000 MTBF (Hours)
Auto Cutter Life	1,500,000 Cuts
Printer Life	15,000,000 Lines
Print Head Life	100 km - 100,000,000 pulses

## Other Features

---

NFC	Near Field Communication available
Cutter	Partial Cut
Sensors	Paper End Sensor, Paper sensor

**What's in the box**

What's in the box	AC adapter, C1, AC cable, Cable fixation saddle, Main unit, Paper spacer, Power switch cover, Roll paper, Setup guide, Warranty document
-------------------	--

**Other**

Warranty	24 months Carry in
----------	--------------------