

## Receiver

<b>Receiver Type</b>	SR 45 Receiver
<b>Carrier Frequency</b>	A / 530 - 560 MHz
<b>Modulation</b>	FM
<b>Audio Bandwidth</b>	40 Hz to 20 kHz
<b>THD &amp; Noise</b>	typ. 0.8%
<b>Signal-to-Noise Ratio</b>	typ. 105 dB(A)
<b>Squelch</b>	-100 to -70 dBm Adjustable
<b>Connections</b>	Balanced XLR and unbalanced 1/4" (6.3 mm) jack: adjustable from mic to line level. Output level at rated deviation: 500 mV rms
<b>Dimensions</b>	7.87 x 7.48 x 1.73" (200 x 190 x 44 mm)
<b>Weight</b>	0.80 lb (360 g)

## Transmitter

<b>Transmitter Type</b>	PT 45 Bodypack
<b>Carrier Frequency</b>	A / 530 - 560 MHz
<b>Modulation</b>	FM
<b>Audio Bandwidth</b>	40 Hz to 20 kHz
<b>THD &amp; Noise</b>	typ. 0.8%
<b>Signal-to-Noise Ratio</b>	typ. 105 dB(A)
<b>RF Output</b>	10 mW
<b>Power</b>	1x 1.5V AA Battery Up to 10 Hours
<b>Dimensions</b>	2.36 x 2.91 x 1.18" (60 x 74 x 30 mm)
<b>Weight</b>	0.13 lb (60 g)