

Overview

Proven reliability

for use in houses of worship, conference rooms and theatres

The DAM Series GN gooseneck modules for permanent screw-on installation are available in three different lengths: 15cm (6in), 30cm (12in), 50cm (20in). Except for the GN30 OC with unterminated cable ends, all come with an in-line XLR phantom power adapter with integrated 250Hz bass rolloff, LED ring and ON/OFF jumper. A mini XLR connector eliminates the need for large holes in the furniture or time-consuming soldering work during installation.

The gooseneck module fits all DAM Series capsules, CK31, CK32, CK33, CK47 and CK80, via highly reliable contacts.

Features

- **Discreet, screw-on mounting module** - for permanent installations
- **Detachable phantom power adapter** - eliminates time-consuming soldering work
- **Special mounting accessories included** - for quick and hassle-free installation
- **Extremely rugged gooseneck construction** - for an extra-long life of reliability and stability
- **Highly reliable contacts for capsule modules** - prevent contact problems and ensure extra-long life

Specifications

General	Audio frequency bandwidth	20 to 20000 Hz
	Bass cut filter	250 Hz
	Recommended load impedance	2000 Ohms
Powering Interface	Voltage	9 to 52 V
	Current	3 mA
Audio Output	Type	Balanced XLR
	Gender	Male
	Contacts	3-pin
Design	Finish	matte dark gray
Dimensions / Weight	Diameter	20 mm