Mackie Onyx Artist Specs

Interface

Channels of I/O	Analog: 2 Inputs / 2 Outputs at 192 kHz
Max Sample Rate/Resolution	192 kHz / 24-Bit
Display and Indicators	2 x LEDs (Clip, Signal) 1 x LED (Host Connection)

Connectivity

Host Connection	1 x USB Type-B (USB 2.0)
Analog I/O	 1 x XLR 3-Pin Balanced Mic Input 1 x 1/4" TRS Balanced/Unbalanced Line/Hi-Z Input 1 x 1/4" TRS Unbalanced Headphone Output 2 x 1/4" TRS Balanced Monitor Output
Phantom Power	+48 V
Digital I/O	None
MIDI I/O	None

Memory Card Slot

None

Performance

Frequency Response Inputs, Outputs:

20 Hz to 20 kHz ±0.5 dB (Min Gain)

Max Input Level Mic Inputs:

+11 dBu (Min Gain) **Line/Hi-Z Inputs:** +24 dBu (Min Gain)

Max Output Level Monitor Outputs:

+10 dBu

Headphone Outputs:

+10 dBu

THD **Mic Inputs:**

Line/Hi-Z Inputs: Monitor Outputs: Headphone Outputs:

EIN Mic/Line/Hi-Z Inputs:

< -100 dB

Monitor Outputs:

< -85 dBu

Headphone Outputs:

< -75 dBu

Digital Audio

Bit Depth	Up to 24-Bit
Sync Sources	Internal

Compatibility

OS Compatibility	macOS Windows
Required Hardware	Available USB 2.0 Port

Power

Power Requirements	USB Bus-Power	

Physical

Anti-Theft Features	Kensington Security Slot
Dimensions	6.42 x 4.49 x 2.01" / 16.3 x 11.4 x 5.1 cm
Weight	1.1 lb / 0.5 kg

Packaging Info

Package Weight	1.86 lb
Box Dimensions (LxWxH)	10.7 x 6.45 x 3.15"