

<p><b>AUDIO</b></p>	<p><b>1-IN / 2-OUT AUDIO INTERFACE WITH 16-BIT DELTA-SIGMA ADC AND DAC (ADC: 48 KHZ – DAC: 48 KHZ), 44,1KHZ / 48KHZ SAMPLE RATE AUDIO QUALITY</b></p> <ul style="list-style-type: none"> <li>• <b>ADC: THD+N = 0.01% / SNR=89DB / DYNAMIC RANGE = 89 DB</b></li> <li>• <b>DAC: THD+N = 0.005% / SNR=96DB / DYNAMIC RANGE = 93 DB</b></li> </ul> <p><b>HIGH SIGNAL – NOISE RELATION SNR = 96 DB</b></p> <p><b>LOW HARMONIC DISTORTION THD+N = 0.01%</b></p> <p><b>BUFFERED BYPASS</b></p>
<p><b>CONNECTORS</b></p>	<p><b>INPUT: 1/4" HIGH-QUALITY BUFFERED INPUT WITH 120DB OF DYNAMIC RANGE (MIC COMPATIBLE WITH A XLR-JACK ADAPTOR)</b></p> <p><b>OUTPUT: 1/4" PRO GRADE STEREO OUTPUTS FOR CONNECTING TO STUDIO MONITORS, D.I.S, P.A. SYSTEM, PEDALS, AMPS, ETC</b></p>
<p><b>INTERFACE</b></p>	<p><b>USB 2.0 COMPATIBLE WITH IOS, ANDROID, MAC AND PC</b></p>
<p><b>MIDI</b></p>	<p><b>COMPATIBLE WITH JAM ORIGIN MIDI GUITAR</b></p>
<p><b>UNBOXED WEIGHT</b></p>	<p><b>0.149KG / 0.328LBS</b></p>
<p><b>UNBOXED DIMENSIONS</b></p>	<p><b>L – 9.2CM/3.62" X W – 3.7CM/1.45" X H – 4.8CM/1.88" (INC. SWITCH)</b></p>
<p><b>POWER</b></p>	<p><b>POWERED BY 9V DC (NOT POWERED BY USB)</b></p>