## REMOTE CONTROL

remote control Type VIDEO Refresh rate 60 Hz CONNECTIONS Type DisplayPort input, HDMI input, LAN, RS-232, USB 2.0, VGA input, audio input, audio output, composite video input, remote control input, remote control output 15 pin HD D-Sub (HD-15), 19 pin HDMI Type A, 20 pin Connector Type DisplayPort, RCA, mini-phone 3.5 mm **MISCELLANEOUS** Compliant Standards CEC, VESA TMDS Color Category black **Included Accessories** batteries Flat Panel Mount Interface 300 x 300 mm TV TUNER **TV Tuner Presence** No **HEADER** Brand **NEC NEC MultiSync Product Line** Model C551 Series C Series TV SYSTEM Additional Features TileMatrix (10 x 10), sync on green, Carbon Footprint Meter, automatic alarm e-mails, Input Labeling, AMX Beacon Compatible, 24/7 Scheduler, NaViSet Administrator 2, screen saver, PJLink, Crestron Roomview support, designed for 24/7 operation **DIMENSIONS & WEIGHT** Width 48.8 in Depth 1.8 in Height 27.9 in Weight 41.45 lbs Comments without stand

## **TELEVISION**

Type
Commercial Use
Commercial Targeting

LED-backlit LCD flat panel display

Yes

digital signage

LCD Display Technology VA

LCD Backlight Technology
LED Backlight Type
LED backlight edge-lit

Video Interface HDMI, composite

HDMI Ports Qty

PC Interface DisplayPort, VGA (HD-15)
Video Wall Components Qty 100

Diagonal Class 55 in
Diagonal Class (metric) 139.7 cm
Resolution 1920 x 1080
Display Format 1080p (Full HD)

Motion Enhancement Technology 60 Hz Refresh Rate

Response Time 8 ms
Image Aspect Ratio 16:9
Image Contrast Ratio 4000:1
Brightness 400 cd/m2

Supported Computer Resolutions 1024 x 768 (XGA), 1152 x 864, 1280 x 1024 (SXGA),

1280 x 720, 1280 x 768 (WXGA), 1280 x 960, 1360 x 768, 1400 x 1050, 1440 x 900, 1600 x 1200 (UXGA), 1680 x 1050 (WSXGA+), 1920 x 1080, 1920 x 1200 (WUXGA), 640 x 480 (VGA), 720 x 400, 750 x 350,

800 x 600 (SVGA), 832 x 624

Additional Features 24/7 Scheduler, AMX Beacon Compatible, Carbon

Footprint Meter, Crestron Roomview support, Input Labeling, NaViSet Administrator 2, PJLink, TileMatrix (10 x 10), automatic alarm e-mails, designed for 24/7

operation, screen saver, sync on green

**AUDIO SYSTEM** 

Output Power / Total 20 Watt
Speaker System 2 speakers

**COMMERCIAL DISPLAY** 

Features SNMP support

**MEDIA PLAYER** 

Supported Memory Cards microSD
USB Port Yes
USB Ports Qty 1

SPEAKER SYSTEM DETAILS

Speaker Type main channel speaker

Speaker Qty 2
Speaker Form Factor built-in
Nominal (RMS) Output Power 10 Watt

CABLE DETAILS

Type VGA cable Length 6 ft

**POWER DEVICE** 

Nominal Voltage AC 120/230 V

Power Consumption Operational	75 Watt
Power Consumption Stand by	0.5 Watt
STANDS & MOUNTS	
Flat Panel Mount Interface	300 x 300 mm
riat i arioi Mount interiace	000 X 000 Hilli
ENVIRONMENTAL STANDARDS	
ENERGY STAR Certified	Yes
ENERGY STAR Version	7.0
DIMENSIONS & WEIGHT (SHIPPING)	
Chinning Width	56.3 in
Shipping Width Shipping Depth	9.8 in
Shipping Depth Shipping Height	36.2 in
Shipping Weight	59.74 lbs
Width (Shipping)	56.3 in
Weight (Shipping)	59.74 lbs
Traigin (ampping)	
DIMENSIONS & WEIGHT DETAILS	
Details	panel with stand, panel without stand
Width	48.8 in
Depth	1.8 in, 10.5 in
Height	27.9 in, 30 in
Weight	41.4 lbs
SERVICE & SUPPORT	
Туре	3 years warranty
SERVICE & SUPPORT DETAILS	
Туре	limited warranty
Service Included	parts and labor
Component (Television)	backlight
Full Contract Period	3 years
ENVIRONMENTAL PARAMETERS	
Min Operating Towns and the	22.°⊏
Min Operating Temperature	32 °F 104 °F
Max Operating Temperature Humidity Range Operating	104 F 20 - 80%
ridificity realige Operating	20 - 00 /0
GENERAL	
Video Interface	Composite, HDMI
PC Interface	VGA (HD-15), DisplayPort
HDMI Ports Qty	3 ports
Power Consumption Operational	75 Watt
Manufacturer	NEC Corporation

## SUSTAINABILITY

ENERGY STAR Certified Yes

## GENERAL

Manufacturer

**NEC** Corporation