

Specifications

MECHANICAL

Dimensions (LxWxH)

66 mm x 67 mm x 108 mm (2.6 in x 2.7 in x 4.3 in)

Weight

170 g (6 oz)

ELECTRICAL

Input Voltage

5 VDC \pm 0.25 V

Operating Power

1.4 W (275 mA @ 5 V)

Standby Power

1.2 W (230 mA @ 5 V)

Host System Interfaces

USB, RS232, Keyboard Wedge, IBM 46xx (RS485), OCIA, Laser Emulation, Light Pen Wand Emulation

ENVIRONMENTAL

Operating Temperature

-20°C to 40°C (-4°F to 104°F)

Storage Temperature

-40°C to 60°C (-40°F to 140°F)

Humidity

5% to 95% relative humidity, non-condensing

Drop

Designed to withstand 1.5 m (5 ft) drops

Environmental Sealing

Sealed to resist airborne particulate contaminants

Light Levels

4842 Lux

SCAN PERFORMANCE

Scan Pattern

Omnidirectional: 5 fields of 4 parallel lines; Button activated single line

Print Contrast

35% minimum reflectance difference

Pitch, Skew

60°, 60°

Decode Capability

Reads standard 1D and GS1 DataBar symbologies

Warranty

3 year factory warranty