

Behringer B-5 Specs

Microphone

Form Factor	Stand/Boom Mount
Sound Field	Mono
Operating Principle	Pressure Gradient Pressure Operated
Capsule	Condenser
Diaphragm	0.71" / 18 mm
Polar Pattern	Cardioid, Omnidirectional
Pattern Selection	Switched
Orientation	End Address
Circuitry	Solid-State
Pad	-10 dB
High-Pass Filter	150 Hz, 6 dB/Octave
Tone Adjustment	<i>None</i>

Indicators	<i>None</i>
On-Board Controls	High-Pass Filter, Pad
Windscreen	Foam (Included)

Performance

Frequency Range	20 Hz to 20 kHz
Maximum SPL	140 dB SPL (Phantom Power) 150 dB SPL (Phantom Power, with Pad)
Impedance	70 Ohms
Load Impedance	1 Kilohms
Sensitivity	Cardioid: -38 dBV/Pa at 1 kHz Omnidirectional: -40 dBV/Pa at 1 kHz
Signal-to-Noise Ratio	Cardioid: 78 dB A-Weighted Omnidirectional: 76 dB A-Weighted
Equivalent Noise Level	Cardioid: 16 dB A-Weighted Omnidirectional: 18 dB A-Weighted
THD	1%

Connectivity

Output Connectors (Analog)	1 x XLR 3-Pin (on Mic)
----------------------------	------------------------

Power

Operating Voltage	48 V (Phantom Power)
Operating Current Consumption	3 mA

Physical

Color	Nickel
Mounting	Mic Clip (Included)
Construction Material	Brass
Dimensions	ø: 0.79 x L: 4.72" / ø: 20 x L: 120 mm
Weight	0.2 lb / 90 g

Packaging Info

Package Weight	1.42 lb
Box Dimensions (LxWxH)	11.95 x 5.2 x 3.3"