

# Behringer B1800XP Specs

## PA Speaker

---

Configuration	Active Subwoofer
---------------	------------------

---

Total Power Capacity	3000 W Peak
----------------------	-------------

---

Amplifier Class	Class-D
-----------------	---------

---

## Drivers

---

LF Driver	<b>1 x 18" / 45.7 cm Woofer</b>
-----------	---------------------------------

---

## Performance

---

Frequency Range	32 Hz to 200 Hz -10 dB
-----------------	------------------------

---

Frequency Response	40 Hz to 150 Hz $\pm 3$ dB
--------------------	----------------------------

---

Maximum SPL	129 dB
-------------	--------

---

Input Sensitivity	+4 dBu (Center)
-------------------	-----------------

---

Max Input Level	+22 dBu (Balanced)
-----------------	--------------------

---

Gain Range	Up to +6 dB
I/O Impedance	<b>Input:</b> 12 Kilohms (Unbalanced) 24 Kilohms (Balanced)
THD	
SNR	>100 dBA
Protections	DC Fault, On/Off Muting, Short Circuit, Thermal

## Connectivity

---

Audio I/O	<b>2 x</b> XLR 3-Pin Balanced Input <b>1 x</b> XLR 3-Pin Balanced Thru/Output <b>1 x</b> XLR 3-Pin Balanced High-Pass Output
-----------	--

## Signal Processing

---

Semi-Parametric EQ	+10 dB at 40 Hz to 90 Hz ⓘ
Filters	<b>Low-Pass:</b> 70 to 150 Hz, 24 dB/Octave Butterworth <b>High-Pass:</b> 100 Hz, 18 dB/Octave Butterworth
Phase Adjustment	0 / 180°

## Power

---

AC Input Power	100 to 120 VAC, 50 / 60 Hz (T 15 A H 250 V)
----------------	---

---

AC Power Connector	<b>1 x IEC</b>
--------------------	----------------

---

Power Consumption	180 W (1/8 Power)
-------------------	-------------------

---

## Physical

---

Dimensions	27.7 x 21.6 x 21.8" / 70.4 x 54.9 x 55.4 cm
------------	---

---

Weight	98.9 lb / 44.9 kg
--------	-------------------

---

## Packaging Info

---

Package Weight	112.5 lb
----------------	----------

---

Box Dimensions (LxWxH)	32.5 x 27 x 27"
------------------------	-----------------

---