

Specification

Cisco 1-Port Serial WAN Interface Card (HWIC-1T)	
Manufacturer	Cisco
Part Number	HWIC-1T
Device Type	Expansion module
Form factor	Plug-in module
Specifications	
Synchronous Support	Yes
Synchronous Maximum Speed (Per Port)	8 Mbps
Asynchronous Support	Yes
Asynchronous Maximum Speed (Per Port)	115.2 kbps
Bisync Support	Yes

Serial Protocols	EIA-232, EIA-449, EIA-530, EIA-530A, V.35, and X.21
Network Clock Synchronization	Yes
NEBS	Type 2/4
TelecommPTT	TBR1 and 2 JATE Digital NEBS
Safety Approvals	UL 60950, CAN/CSA 22.2, CSA60950, GB 4943, AS/NZS 60950, EN60950, IEC 60950
Immunity	EN300386, CISPR24, EN55024, EN50082-1, 61000-4-2/3/4/5/6/8/11
Emissions	FCC Part 15 Class A, ICES-003 Class A, EN55022 Class A, CISPR22 Class A, AS/NZSCISPR22 Class A, VCCI Class A, EN 300386, EN61000-3-2/3, CNS13438
Physical Specifications	Singlewide HWIC, no slot restrictions Dimensions (H x W x D) 0.8 x 3.1 x 5.6 in. (2.1 x 7.9 x 14.2 cm)
Environmental Specifications	Operating temperature: 32 to 104°F (0 to 40°C) NEBS short-term operating temperature: 32 to 131°F (0 to 50°C) Storage temperature: -4 to 149°F (-20 to 65°C) Relative humidity: 10 to 90%, noncondensing