



## SRX-50DX/50XT

### 50 WATTS

A compact general purpose speaker column using two Full Range Dual Cone 8" speakers, reproducing a clean undistorted sound for both speech and music. The system is housed in a Rugged Closed Box Enclosure made of 12mm medium density fibre board, and has a durable black shock resistant paint finish. SRX-50DX has nominal impedance of 16 $\Omega$ , SRX-50XT operates on 100V line with three power taps selectable through a rotary switch.

SPECIFICATIONS	SRX-50DX	SRX-50XT
INPUT POWER	50W Max.	50W Max.
POWER TAPS	—	30/20/10W at 100V
CONFIGURATION	One Way	One Way
FREQUENCY RESPONSE	55-16,000Hz	55-16,000Hz
LOW FREQUENCY SPEAKER	2 x 8", $\varnothing$ 0.75" Voice Coil	2 x 8", $\varnothing$ 0.75" Voice Coil
HIGH FREQUENCY UNIT	—	—
SPL at (1W/1m)	96dB	96dB
MAX. RATED SPL	113dB	113dB
NOMINAL IMPEDANCE	16 $\Omega$	333/500/1k $\Omega$
PORT	Sealed Enclosure	Sealed Enclosure
INPUT CONNECTORS	Two nos. of Terminal Strip in parallel	—
DIMENSIONS	W325 × H585 × D240 mm	W325 × H605 × D240 mm
WEIGHT	8.90kg	9.30kg