

Audio-Technica Pro 45 Specs

Microphone

Form Factor	Hanging
Sound Field	Mono
Capsule	Condenser
Polar Pattern	Cardioid
Orientation	End Address
Circuitry	Solid-State
Pad	<i>None</i>
High-Pass Filter	<i>None</i>

Performance

Frequency Range	70 Hz to 16 kHz
Maximum SPL	134 dB SPL (1 kHz, 1% THD)
Impedance	100 Ohms
Sensitivity	-37 dB

Dynamic Range	106 dB (1 kHz, at Max SPL)
Signal-to-Noise Ratio	66 dB A-Weighted (1 kHz, at 1 Pa/94 dB SPL)

Connectivity

Output Connectors (Analog)	1 x XLR 3-Pin Male (on Attached Cable)
Cable Length	25' / 7.62 m
Wireless Connectivity	<i>None</i>

Digital Audio

Digital Signal Processing	<i>None</i>
---------------------------	-------------

Power

Operating Voltage	9 to 52 V (Phantom Power)
Operating Current Consumption	2 mA (Phantom Power)

Physical

Color	Black
Mounting	Hanging

Dimensions

ø: 0.47 x L: 2.24" / ø: 12 x L: 56.9 mm

Weight

0.5 oz / 15 g