

Technical specifications

Product	
Part Number	T2G-D3D-IF
Connectivity	
Video Input	Connectors: 1 DVI-DL input or 1 VGA input
Video Output	Connectors: 2 or 3 DVI-I outputs (connects to digital or analog)
Multi-Unit Support	Yes (available under Windows only)
Performance	
Video Output Resolutions	DVI* 5760x1080 (3x 1920x1080)** 4080x768 (3x 1360x768) 3840x1200 (2x 1920x1200) VGA* 4080x768 (3x 1360x768) 5040x1050 (3x 1680x1050) *Maximum resolution is system dependent - please see the system compatibility information **This mode runs at 50Hz which may be incompatible with some displays. Verify with your display vendor for compatibility.
Video and Audio Processing	
Non-Rectangular/Artistic Video Walls	No

Clone Mode	No
Bezel Management	Yes (available under Windows only)
Stretched Desktop Support	Yes
Physical	
Product Dimensions	4.4 (L) x 5.5 (W) x 1.1 (H) inches
Unit Weight	0.573 lbs / 260 g
Power Supply Unit	USB for power
Hardware & Software	
Hardware Included	One USB cable One 2-foot HD-15-to-HD-15 (analog) input cable DVI-DL to DVI-DL input cable
Accessories (sold separately)	Power Supply Kit (Part # GXM-PSKIT-IF) DVI-to-VGA Adapter (ADP-DVI-AF) - DVI (male) to HD15 (female) adapter
Software	Matrox PowerDesk (free download)
General	

System Requirements	Dual-link DVI or single VGA output connector, on a compatible system Display Driver supporting 3072 x 768 or higher resolution Powered USB connector
Supported Operating Systems (software)	Windows 10 Windows 10 x64 Windows 7 Windows 7 x64 Windows 8 Windows 8 x64 Windows 8.1 Windows 8.1 x64 Windows Server 2003 Windows Server 2003 x64 Windows Server 2008 Windows Server 2008 R2 Windows Server 2008 x64 Windows Server 2012 Windows Server 2012 R2 Windows Vista Windows Vista x64 Windows XP Windows XP x64 OS X 10.10 Yosemite OS X 10.11 El Capitan OS X 10.7 Lion OS X 10.8 Mountain Lion OS X 10.9 Mavericks Mac OS X 10.6 Snow Leopard