

Matrox G55+MDHA32DSF Specs

Device Type	Graphics adapter
Enclosure Type	Plug-in card
Card Type	AGP 4x, compatible with all AGP slots (0.8, 1.5 or 3.3 V)
Card Form Factor	ATX
Bracket Form Factor	ATX
API Supported	DirectX
Memory	
Video Memory	32 MB
Technology	DDR SDRAM
Performance	
RAMDAC Clock Speed	360 MHz
Maximum Resolutions (Per Display)	Digital: 1280 x 1024 Analog main display: 2048 x 1536 Analog secondary display: 1600 x 1200
Max Monitors Supported	2

Interfaces / Ports

Interfaces	1x DVI-I - 29-pin combined DVI 1x VGA - 15-pin HD D-Sub (HD-15) 1x VGA - 15-pin HD D-Sub (HD-15) (with adapter) 1x S-video / composite output (on supplied cable)
------------	--

I/O Expansions

Compatible Slots	1x AGP
------------------	--------

Environmental Requirements

Operating Temperature	32 - 131°F (0 - 55°C)
-----------------------	-----------------------

Humidity Range	20 - 80%
----------------	----------

System Requirements

Peripheral / Interface Devices	CD-ROM
--------------------------------	--------

General

Compliant Standards	CE, CSA, VCCI, DDC-2B, VESA DPMS, EMC, FCC, ACA
---------------------	---

Dimensions (LxH)	6.6 x 3.2" (16.76 x 8.12 cm)
------------------	------------------------------

Weight	<i>Not specified by the manufacturer</i>
--------	--

Packaging Info

Package Weight	0.55 lb
----------------	---------

Box Dimensions (LxWxH)	8.8 x 6.3 x 1.4"
------------------------	------------------