

Model Configuration

Model	3330/DNI
Print speed	up to 42 ppm
Duty cycle	Up to 80,000 images/month ^①
Recommended monthly print volume	Up to 6,000 pages
Two-sided output	Standard
First-page-out time, printing	As fast as 6.5 seconds
Maximum print resolution	600 x 600 dpi (up to 1200 x 1200 enhanced image quality)
Processor speed	1.0 GHz
Print memory (standard/max)	512 MB / 512 MB
Connectivity	10/100/1000 BaseT Ethernet, USB 2.0, Wi-Fi
Page Description Languages (PDL)	JPEG, PCL [®] 5e, PCL [®] 6, PDF Direct, PostScript 3 compatible, TIFF
Print features	Automatic 2-sided, Booklet printing, Collation, Custom page size, Draft mode, Earth Smart, Fit-to-page, Job scheduling, MICR, N-up, Poster printing, Print from USB, Print from local drive, Save, Save and Print, Scaling, Watermarks

Model	3330/DNI
Mobile printing	<u>Apple® AirPrint™, Google Cloud Print™, WiFi Direct</u> (optional: <u>Xerox® Print Service Plug-in for Android™</u>)
Warranty	One-year Quick Exchange
Price	\$279 ^①
	<div style="border: 1px solid red; padding: 5px; display: inline-block; margin-bottom: 10px;">ADD TO CART</div> <div style="border: 1px solid black; padding: 5px; display: inline-block;">OTHER WAYS TO BUY</div>

Device Management

Device management features	Apple® Bonjour, Email alerts, Xerox® CentreWare® Internet Services, Xerox® CentreWare® Web
-----------------------------------	--

Print Drivers

OS support	Mac OS® version 10.8 and later, Windows® Vista® and later, Xerox® Global Print Driver®, Xerox® Mobile Express Driver®, various Linux® and Unix® distributions
-------------------	---

Paper Handling

Output capacity	150 sheets
Paper capacity	Tray (Bypass tray): 50 sheets Tray 1: 250 sheets Tray (optional): 550 sheets

Paper size	Tray (Bypass tray): Custom sizes: 3 x 5 in. to 8.5 x 14 in. (76 x 127 mm to 216 x 356 mm) Tray 1 : Custom sizes: 3.9 x 5.8 in. to 8.5 x 14 in. (99 x 147 mm to 216 x 356 mm) Tray (optional): Custom sizes: 3 x 5 in. to 8.5 x 14 in. (76 x 127 mm to 216 x 356 mm)
-------------------	--

Security

Security features	IP filtering, IPSec, IPv6, SNMPv3, SSL, Secure HTTPS (SSL/TLS), Secure IPP, WEP (64-/128-bit), WPA/WPA2-Enterprise, WPA/WPA2-Personal, WPA2-PSK (AES)
--------------------------	---

Operating Environment

Temperature (operating)	50 - 90 ° F (10 - 32 ° C)
Temperature (non-operating)	32 - 104 ° F (40 - ° C)
Relative humidity (operating)	20 - 80 % RH (noncondensing)
Sound pressure levels	54 dB (operating), 26 dB (standby)
Warm-up time (from power save mode)	11.5 seconds

Electrical

Power consumption	Operating: 700 W Standby: 50 W
--------------------------	-----------------------------------

	Power save: 3.5 W
ENERGY STAR	ENERGY STAR® qualified

Dimensions

Dimensions (WxDxH)	14.4 x 14.4 x 11.4 in. (366 x 366 x 290 mm)
Weight	28.33 lb (9.9 kg)

Certifications

Certifications	CE Mark applicable to Low Voltage Directive (2006/95/EC), EMC Directive 2004/108/EC, FCC Part 15, Class B, FCC Part 68, GOST, GS Mark, R&TTE Directive 1999/5/EC, UL 60950-1/CSA 60950-1-07, 2nd Edition
Sustainability	<u>EPEAT</u> <u>ENERGY STAR®</u>