

Spec description

Microphone type	Cardioid
Frequency range	50Hz to 20kHz
Input output ratings	
Maximum input level	120dB SPL (at 1kHz, SENS: H, LCF=Flat, RL: 2.2k Ω , Vcc: 2.5V)
Output impedance	1.6k Ω (RL: 2.2k Ω , Vcc: 2.5V)
S/N ratio	74dB (at 1kHz, 1Pa, A weighted)
Mic sensitivity switch	SENS H:-37dB, SENS L:-52dB (at 1kHz, 0dB=1V/Pa, RL: 2.2k Ω , Vcc: 2.5V)
Connection cable/plug	
Cable length	13" / 33 cm
Plug	1/8" (3.5mm) TRS Stereo Mini plug (Tip: L-ch, Ring: R-ch, Sleeve: GND) $\times$ 1
Power	Plug-in power (JEITA standard CP-1203A)
Dimensions (W $\times$ H $\times$ D)	
TM-2X main unit	2.24" $\times$ 2.3" $\times$ 2.7" / 57 $\times$ 59 $\times$ 69 mm (excluding cable and connectors)
Noise isolation arm	1.34" $\times$ 2.24" $\times$ 5.6" / 34 $\times$ 57 $\times$ 142 mm
Weight	
TM-2X main unit	2.4 oz. / 75 g
Noise isolation arm	1.5 oz. / 41 g
Operating temperature	23°F to 142°F / -5° to 45°C
Accessories	Fur windscreen, Noise isolation arm, Owner's Manual, Warranty