

Spec description

Format	
Sampling frequency	44.1k/48k/88.2k/96k Hz
Bit length	16-bit/24-bit
Analog output 1-8/9-16	
Connector	D-Sub 25-pin
Locking screws	No.4-40 UNC (inch type)
No. of output channels	16
Nominal output level / maximum output level	+4dBu/+24dBu +4dBu/+22dBu +4dBu/+20dBu +4dBu/+18dBu +6dBu/+15dBu
Output impedance	200 Ω
Output attenuation	0 <> -14dB (0.5dB steps)
Applicable load impedance	2k Ω or more
Dimensions	107(W) $\times$ 40(H) $\times$ 161.5(D)mm
Weight	240g
Accessories	Owner's manual (with warranty)

Audio performance

Frequency response	+0.1dB/-0.5dB:20Hz/20kHz (-16dBFS input, Fs=44.1k/48kHz, JEITA) +0.1dB/-1.0dB:20Hz/40kHz (-16dBFS input, Fs=88.2k/96kHz, JEITA)
THD	0.001% or less (0dBFS input, 1kHz, Fs=44.1k/48k/88.2k/96kHz, JEITA)
S/N ratio	110dB or more (Fs=44.1k/48k/88.2k/96kHz, JEITA)
Dynamic range	110dB or more (Fs=44.1k/48k/88.2k/96kHz, JEITA)
Crosstalk	110dB or more (1kHz, Fs=44.1k/48k/88.2k/96kHz, JEITA)