

Model Configuration

Model	6025V_BI
Print speed	Colour: up to 10 ppm Black: up to 12 ppm
Duty cycle	Up to 30,000 images/month ^①
Processor speed	525 MHz
Print memory (standard)	256 MB standard
Connectivity	High-Speed USB 2.0, Wi-Fi Direct, Wi-Fi b/g/n
Maximum print resolution	Up to 1200 x 2400 dpi enhanced image quality
First-page-out time, printing	As fast as 19 seconds colour / 19 seconds black and white
Page Description Languages (PDL)	GDI
Print features	Auto Screening (Standard, Fineness, Gradation), Bi-directional driver, Collation, Color Balance Adjust, Custom page size, Draft mode, Fit-to-page, Image Options (Standard, Photos, Presentation, Design, POP), Job Monitoring, N-up, PANTONE® Colour calibrated solid-color simulations, Reduce/Enlarge, Scaling
Mobile printing	<u>Apple® AirPrint™</u> , <u>Mopria® Certified</u> (optional: <u>Xerox® Wireless Print Solutions Adapter</u> – includes Apple AirPrint, <u>Google Cloud Print™ v2.0</u> and Mopria)

Copy

Maximum copy resolution	Up to 600 x 600 dpi
First-page-out time, copying	As fast as 40 seconds colour / 24 seconds black and white
Copy features	Auto exposure, Collation, Colour balance, Edge erase, ID Card Copy, Lighter/Darker, Reduce/Enlarge, Sharpness

Scan

Scan features	Black and white, Colour, Greyscale, Image-only PDF/Multi-Page TIFF /Single-page TIFF/ JPEG
Scan destinations	Application (TWAIN USB/Network), Mac 10.6 or later (USB/Network/MacIICA), Scan to Network Computer (SMB/ FTP), Scan to USB, Scan to email, WIA (USB/WSD Scan), WSD

Security

Security features	IP filtering, IPv6, Network Address Book Authentication (LDAP, Windows Kerberos), SSL, Secure HTTP (SSL/TLS), Secure IPP, WEP (64/128 bit), WPA2-PSK (AES), and WPA/WPA2-PSK (Mixed Mode)
--------------------------	---

Print Drivers

OS support	Fedora Core 15-17, Mac OS® version 10.5 or higher, Redhat Enterprise 4 and 5, SUSE® 11, 12, Ubuntu®, Windows Server 2012, Windows® 2003 Server, Windows® 2008 Server, Windows® 7, Windows® 8, Windows® 8.1, Windows® XP
-------------------	---

Media Handling

Document handler	Platen cover
Paper capacity	Tray (Bypass tray): 10 sheets Tray (Main tray): 150 sheets
Paper size	Tray (Bypass tray): Custom sizes: 76 x 127 mm to 216 x 356 mm Tray (Main tray): Custom sizes: 76 x 127 mm to 216 x 356 mm
Output capacity	100 sheets

Electrical

Power consumption	Operating: 220 W Standby: 45 W Power save: 10 W
ENERGY STAR	ENERGY STAR® qualified

Operating Environment

Temperature (operating)	10 - 32 ° C
Relative humidity (operating)	10 - 85 % RH (noncondensing)

Dimensions

Minimum	410 x 389 x 318 mm
----------------	--------------------

dimensions (WxDxH)	
Weight	14.5 kg (min)

Certifications

Sustainability	<u>EPEAT</u>
-----------------------	---------------------