Full Description

Features

- · 2.4 GHz wireless audio playback
- · Four mono microphone/line input channels
- Four 1/4" stereo line input channels
- Accepts balanced and unbalanced input connections
- · Connect up to 2 wireless microphones or any bluetooth audio device
- Control room/Phones source matrix for monitor flexibility
- EFX/AUX send cue for monitoring individual channel
- 75Hz low-cut filter on mono channel for removing rumble
- Versatile 100 EFX with 8 tap effects and test tones
- Balanced master output
- Global +48V phantom power
- Ideal for sub mixes, small performances and studio application

Specifications

- Total Channels: 12
- Balanced Mono Mic / Line Channel: 4
- Aux Return: 2 Stereo2T Input: Stereo RCA
- Main L/R Stero Output: 2 x 1/4" TRS, Bal.
- Aux/Efx Send: 1 x 1/4" TRS, Bal.
- Rec Out: Stereo RCACTRL RM L/R: 2 x 1/4" TS
- Phones: 1
- Channel Strips: 6
- Aux/Efx Send Strips: 2
- Pan/Balance Control: Yes
- Volume Controls: Rotary
- Inserts: 4
- Phones Level Control: Yes
- Main L/R Level Control: 60mm Fader
- Number Of Metering Channels: 2
- Segments: 4
- Phantom Power Supply: +48V DC
- Frequency Response (Mic input to any output) 20Hz 60KHz: +0/-1 dB
- 20Hz 100KHz: +0/-3 dB
- Mic Preamp Input: +10 dBu
- All Other Input: +21 dBu
- Balanced Output: +28 dBu