ClearOne 930-3200-010-I Specs

Beamforming Microphone

Microphone	24-Microphone Array Number of Beams: Two patterns, either 5 or 6 Beams Polar Pattern: Custom Frequency Response: 150 Hz to 16 kHz, ±3 dB Dynamic Range: 150 Hz to 16 kHz, >70 dB
Amplifier Output	Type: 0.2" / 5.1 mm Black Header, Male, Phoenix- Type Euroblock Audio: 2 Channels Output Power: 2 x 10 W Max, 8-Ohm Load Frequency Response: 20 Hz to 22 kHz at +10 dBu, ±0.5 dB
Configuration	Acoustic Echo Cancellation (AEC) On/Off Noise Cancellation (NC) On/Off Automatic Level Control (ALC) On/Off Gain Adjust Mute On/Off
Software	Console Al Lite Software for Configuration and Administration
Mounting	Ceiling Mount (23.6" / 600mm Tile Grid)
Dimensions	23.33 x 23.33 x 2.13" / 592.5 x 592.5 x 54.1 mm
Weight	7.7 lb / 3.5 kg

USB Extender

Extender Port Type: USB Type-B Connector

Audio: Digital Audio, 2 x 2 Bidirectional Channels

Sample Rate: 48 kHz Sample Bit Depth: 24-Bit Compatible: USB 2.0, USB 3.0 USB Cable Distance: 16' / 5 m

Compatibility: Windows, Mac OS Devices

Link

P-Link In & Out: Proprietary Network

Ports Type: RJ-45 (Cat 5e/6)

Cable: RJ45 Solid Core 24 AWG, Factory-Terminated

(Cat 5e/6)

Distance: Up to 200' / 60 m

Power Switch

Type: Slide Switch

Slide Toward P-Link to Power Device by P-Link Slide Toward PoE to Power Device by PoE Injector

Power and Thermal

Power Type: PoE, PoE+

Port Type: RJ-45

PoE In/P-Link In: 802.3af or 802.3at PoE/PoE+Power Source: PoE Injector or Equivalent

PoE: IEEE802.3at Compliant Devices Providing 56 V

and 640 mA (36 W) P-Link In - Mode B

Power Consumption:

100 to 240 VAC, 50/60 Hz, 3 W Typical 38 W at Max Power 1 kHz (2 x 10 W)

Thermal:

130 BTU/Hr at Max Power

Operating Temperature:

14 to 104°F / -10 to 40°C Ambient Temperature

Mounting

Rackshelf Mount

Under-the-Table Mount

Wall Mount Ceiling Mount

Dimensions ($W \times D \times H$)

Without Rack Ears: 5.5 x 1.6 x 4.1" / 14.4 x 4.2 x 10.3

cm

With Rack Ears: 6.8 x 1.7 x 4.1" / 17.2 x 4.3 x 10.3 cm