

ClearOne 930-6200-206-W-A Specs

Acoustic Characteristics	Element: Condenser (Electret) Polar Pattern: 3 x 120° Cardioid Patterns, Covering 360° Signal/Noise Ratio: 74 dBA at 1 kHz Frequency Response: 70 Hz to 20 kHz Sensitivity: -37 dB at 1 kHz (0 dB = 1 V / Pa) Max Sound Pressure Level: 120 dB SPL RF Immunity: 100% Immunity, Fully Balanced Twisted Pair Throughout
Power and Thermal	DC Power: 9 VDC at 0.5 A Impedance: 200 Ohms Operating Temperature: 41 to 104°F / 5 to 40°C
Cables	Junction Box to Interface Box: RJ45 Cat 5e/6 24 AWG (Max 200' / 61 m) Junction Box to Mic Capsule: Proprietary Mic Array Cable (Max 7' / 2.1 m)
Compliance	FCC, IC, CE, RoHs, WEEE, UL2043 (Plenum Rated)
Dimensions (W x D x H)	Mic Capsule: 1.7 x 1.7 x 86.6" / 43.2 x 43.2 x 2199.6 mm Analog-X Interface: 6.8 x 4.1 x 1.7" / 172.7 x 104.1 x 43.2 mm Analog-X Junction: 4 x 3.7 x 1.4" / 101.6 x 94 x 35.6 mm
Weight	Mic Capsule: 6 oz / 170.1 g Analog-X Interface: 13 oz / 368.5 g Analog-X Junction: 6.5 oz / 184.3 g