Shure MV7 Specs

Microphone

Primary Applications	Podcast, Audio for Video
Form Factor	Desktop
Intended Sound Sources	Vocals
Sound Field	Mono
Capsule	**1 x** Dynamic
Polar Pattern	Unidirectional
Orientation	End Address
Circuitry	Solid-State
High-Pass Filter	*None*
Gain Adjustment	0 to +36 dB
On-Board Controls	Gain/Sensitivity, Headphone Volume, Mic Mute
Windscreen	Built-In

Performance

Frequency Range	20 Hz to 20 kHz

Maximum SPL	**Unidirectional:** 132 dB SPLⓘ
Impedance	**Unidirectional:** 314 Ohms at 1 kHzⓘ
Sensitivity	**Unidirectional:** -55 dBV at 1 kHz **Unidirectional:** -47 dBFS/Pa at 1 kHzⓘ

Connectivity

Output Connectors (Analog)	**1 x** XLR 3-Pin Male (on Mic)
Output Connectors (Digital)	**1 x** USB Type-B Female (on Mic)
Headphone Connector	**1 x** 1/8" / 3.5 mm
Cable Length	10' / 3.0 m (Straight)

Digital Audio

A/D Conversion	16 / 24-Bit
Sample Rate	Up to 44.1 / 48 kHz
Operating System Support	Android, Windows, iOS, macOS/OS X
Mobile Device Compatibility	iPad or Later iPhone 6th Gen. or Later iPod
RAM Requirement	2 GB Minimum

Power

Bus Power	USB / Lightning