

Overview

Lead time

Usually in Stock

General

provided equipment

User manual

Physical

cable length

2.00 m

colour

White

depth

11.03 cm

height

6.17 cm

product weight

0.76 kg

width

27.15 cm

Input

network frequency

50 Hz +/- 5 Hz

plug standard

BS1363A British

maximum input current

13 A

switching current capacity

13 A

input voltage

230 V

Output

number of power socket outlets

6

Outlet standard

BS 1363 United Kingdom

Conformance

product certifications

CE

equipment protection policy

Lifetime : 50000 euros

Environmental

ambient air temperature for operation

0...40 °C

relative humidity

0...90 %

operating altitude

0...10000 ft

ambient air temperature for storage

-5...40 °C

storage Relative Humidity

Non-condensing 0...95 %

storage altitude

0.00...4572.00 m

Surge Protection and Filtering

Common mode rejection

40 dB

peak current

48 kA common mode

24 kA normal mode

Surge energy rate

1836 J

Packing Units

Package 1 Weight

0.88 kg

Package 1 Height

6.5 cm

Package 1 width

31 cm

Package 1 Length

16.5 cm

SCC14

10731304313981

Number of Units in Package 2

12

Package 2 Weight

9.12 kg

Package 2 Height

355.60 mm

Package 2 width

330.20 mm

Package 2 Length

415.80 mm

Number of Units in Package 3

192