Mackie EM-91CU+ Specs

Microphone

Primary Applications	Studio Recording, Podcast, Web-Streaming, Conferencing	
Form Factor	Desktop / Stand/Boom Mount	
Intended Sound Sources	Vocals, Speech/Voice Over, Instrument	
Sound Field	Mono	
Operating Principle	Pressure Gradient	
Capsule	Electret Condenser	
Diaphragm	0.6" / 14 mm	
Polar Pattern	Cardioid	
Orientation	Side Address	
Circuitry	Solid-State	
Pad	None	
High-Pass Filter	None	
Tone Adjustment	None	
Gain Adjustment	None	

Indicators	1 x Green/Red Single LED (Mute, Power)	
On-Board Controls	Mic Mute	
Windscreen	None	

Performance

Frequency Range	30 Hz to 18 kHz
Maximum SPL	132 dB SPL (1 kHz, 1% THD)
Sensitivity	-32 dBV/Pa at 1 kHz
Signal-to-Noise Ratio	78 dB
Equivalent Noise Level	16 dB A-Weighted

Connectivity

Output Connectors (Analog)	None
Output Connectors (Digital)	1 x USB Type-B Female (on Mic)
Headphone Connector	1 x 1/8" / 3.5 mm
Wireless Connectivity	None
Bluetooth	None

Digital Audio

A/D Conversion	16 / 24-Bit
Sample Rate	48 / 96 kHz
Operating System Support	Windows, macOS/OS X
Mobile Device Compatibility	None
Available Port	USB (Interface Unspecified)

Power

Bus Power	USB
Operating Voltage	Not Specified by Manufacturer

Physical

Color	Gray
Mounting	Shockmount (Included)
Included Case	None
Included Filters	None
Dimensions	ø: 1.7 x L: 6.3" / ø: 4.3 x L: 16 cm
Weight	0.5 lb / 0.2 kg