Quick Specs

Device Type

White LED edgelight system

Features

USB 3.2 Hub

Panel Type

In-Plane Switching Technology

Aspect Ratio

16:9

Native Resolution

1920 x 1080 at 60 Hz

Pixel Pitch

0.2745 mm x 0.2745 mm

Brightness

250 cd/m² (typical)

Contrast Ratio

1000:1 (typical)

Response Time

5 ms typical (Fast) (gray to gray) 8 ms (Normal mode) (gray to gray)

Color Support

16.7 Million

Input Connectors

1 x HDMI 1.4 (HDCP 1.4)

1 x DisplayPort 1.2 (HDCP 1.4)

1 x VGA

1 x SuperSpeed USB 5 Gbps (USB3.2 Gen 1) upstream

4 x SuperSpeed USB 5 Gbps (USB3.2 Gen 1)

Display Position Adjustments

Height adjustability stand 150 mm Tilt -5° to 21° Swivel -45° to 45° Pivot -90° to 90°

Screen Coating

Anti-Glare

Dimensions (WxDxH) - with stand

21.17 inches x 7.07 inches x 19.53 inches

Compliant Standards

ENERGY STAR certified monitor.

EPEAT Gold registered in the U.S. EPEAT registration varies by country. See www.epeat.net for registration status by country.

RoHS-compliant.
TCO Certified Edge
BFR/PVC free monitor (excluding external cables).
Meets NFPA 99 leakage current requirements.
Arsenic-free glass and Mercury-free for the panel only.

Product Description

Dell 24 Monitor - P2422H

Diagonal Size

23.8 inches

Weight

7.47 lbs

See less

General

Display Type

LED-backlit LCD monitor / TFT active matrix

Diagonal Size

23.8"

Built-in Devices

USB 3.2 Gen 1 hub

Panel Type

IPS

Aspect Ratio

16:9

Native Resolution

Full HD (1080p) 1920 x 1080 at 60 Hz

Pixel Pitch

0.2745 mm

Pixel Per Inch

93

Brightness

250 cd/m²

Contrast Ratio

1000:1

Color Support

16.7 million colors

Response Time

8 ms (gray-to-gray normal); 5 ms (gray-to-gray fast)

Horizontal Viewing Angle

Vertical Viewing Angle

178

Screen Coating

Anti-glare

Backlight Technology

WLED

Features

LED edgelight system, 99% sRGB color gamut, Flicker Free technology, Mercury free, arsenic-free glass, Dell ComfortView Plus

Dimensions (WxDxH)

21.2 in x 7.1 in x 19.5 in - with stand

Connectivity

Interfaces

- DisplayPort
- VGA
- HDMI
- USB 3.2 Gen 1 upstream
- 4 x USB 3.2 Gen 1 downstream

Mechanical

Display Position Adjustments

Height, pivot (rotation), swivel, tilt

Tilt Angle

-5/+21

Swivel Angle

90

Rotation Angle

180

Height Adjustment

5.9 in

VESA Mounting Interface

100 x 100 mm

Miscellaneous

Features

Security lock slot (cable lock sold separately), VESA interface support

Cables Included

- 1 x DisplayPort cable DisplayPort to DisplayPort 6 ft
- 1 x USB 3.2 Gen 1 upstream cable

Compliant Standards

RoHS, DisplayPort 1.2, BFR-free, HDCP 1.4, PVC-free

Power

Input Voltage

AC 100-240 V (50/60 Hz)

Power Consumption (On mode)

12 W

Power Consumption Stand by

0.3 Watt

Power Consumption Sleep

0.3 Watt

Power Consumption (Off Mode)

0.2 Watt

On / Off Switch

Yes

Dimensions & Weight

Dimensions & Weight Details

- With stand width: 21.2 in depth: 7.1 in height: 19.5 in
- Without stand weight: 7.4 lbs

Dimensions & Weight (Shipping)

Shipping Weight

17.53 lbs

Environmental Standards

ENERGY STAR Certified

Yes

Manufacturer Warranty

Bundled Services

3 years Advanced Exchange Service and Limited Hardware Warranty