Product Information

EAR No. 0M 10 PHONE—UN 0M 10 PHONE—UN 0M 10 PHONE—UN 0M 10 PHONE—UN 0M 40 4415903167 4 40 4415903167 4 40 4415903167 4 40 4415903167 4 40 4415903167 4 0 40 4415903167 4 0 40 4415903167 4 0 50 443 1 50 442 5 1 50 1 50 1 20 1 50 1 20 1 50 1 20 1 50 1 20 1 50 1 20 1 50 1 20 1 50 1 20 1 2					
Mark No. 40.441550116.13 40.441550116.5 6.1510418.6 7 40.441550116.7 40.44155	Product name	DW Office PHONE - EU	DW Office PHONE – UK	DW Office PHONE - US	DW Office PHONE - AUS
DPC No.	Order name	DW 10 PHONE – EU	DW 10 PHONE – UK	DW 10 PHONE – US	DW 10 PHONE – AUS
Product description	EAN No.	40 4415505164 3	40 4415505165 0	40 4415505166 7	40 4415505167 4
Product description	UPC No.	6 1510418160 1	6 1510418162 5	6 1510418163 2	6 1510418164 9
DECT for US	Art. No.	504430	504431	504432	504433
BECT for US DECT CAT-Ing (1.880 to 1.900 MHz) GAP compatible Ves (Headset) Base Station Connects to base station Headset Auto Link to Base Yes, can be activated on the base station Firequency response Margelinement For exercit vestion places check Semhelser Updater. Please refer to sennheiser.com/cco/software BIS (Electronic Hook Switch) Ves (accessory – order EHS adapter separately) Micraphone Frequency response Wideband Mode 150 Hz – 6.8 KHz Frequency response Wideband Mode 150 Hz – 6.8 KHz Yes Frequency response Wideband Mode Neodymium Magnet Speaker 150 Hz – 6.8 KHz Speaker type Neodymium Magnet Speaker 150 Hz – 6.8 KHz Frequency response Narrowband Mode 30 Hz – 3.5 KHz General Data Neodymium Magnet Speaker General Data 20 °C to ± 7.0° C (~4° to ±158 °F) Weight, nearbook version 24 g / 0.86 oz Weight, headhand version 50 g / 1.76 oz Ear pad Size 30 mm / 1.96 in Battery (Lithium Polymer) Exchangeable for service (see User manual) Yes with nameplate on headset 180 my / 500 ft Range –	Product description	Wireless DECT headset (single-sided) with base station for desk phone; convertible (headband or ear hook)			
DECT for US DECT 6.0 (1.9 20 to 1.9 30 MHz) CAP compatible Yes (leadest) Headset Connects to desk phone Base Station Connects to desk phone Headset Auto Link to Base Yes, can be activated on the base station Firmware requirement For newest version please check sennheiser Updater. Please refer to sennheiser.com/cco/software EHS (Electronic Hook Lifter) HSI 10 (accessory – order separately) Microphone HSI 10 (accessory – order separately) Frequency response Wideband Mode Frequency response Narrowband Mode Wite Microphone HSI 10 (accessory – order separately) Speaker Neodymlum Magnet Speaker Frequency response Wideband Mode Frequency response Wideband Mode HSI 10 (accessory – order separately) General Data Neodymlum Magnet Speaker General Data Hoodymlum Magnet Speaker General Data HSI 10 (accessory – order separately) Weight, backhold Mode Story (Preguency response Narrowband Mode Story – order separately) Hoodymlum Magnet Speaker Frequency response Narrowband Mode Story – order separately (Preguency response Narrowband Mode Story – order separately) Hoodymlum Magnet Speaker Battery (Lithlum Polymer) Extra pagnet In a separately (Preguency re	Technical Data				
GAP compatible Yes (Headset) Connects to base station Base Station Connects to desk phone Headset Auto Link to Base Yes, can be activated on the base station Firmware requirement Prevenery response Wideband Mode Yes (accessory – order EHS adapter separately) Microphone Microphone 150 H2 − 6.8 KHz Frequency response Wideband Mode Frequency response Narrowband Mode Frequency response Narrowband Mode Frequency response Narrowband Mode Frequency response Wideband Mode Frequency response Wideband Mode Frequency response Wideband Mode Frequency response Wideband Mode Frequency response Narrowband Mode Prequency response Narrowband Mode Frequency response Narrowband Mode Prequency response Narrowband Narrowband Narrowband Narrowband Narrowband Narrowband Narrowband Narrowband Narrow Prepared Narrow Prepared Narrow Narrow Narro	DECT for EU, UK, AUS	DECT CAT-iq (1.880 to 1.900 MHz)			
Bease Station Connects to base station Base Station Connects to desk phone Headset Auto Link to Base Yes, can be activated on the base station Firmware requirement For newest version please check Sennheiser Updater. Please refer to sennheiser.com/cco/software ERS (Electronic Hook Switch) Ves (accessory – order separately) Microphone 15. 10 (accessory – order separately) Frequency response Wideband Mode Frequency response Wideband Mode Frequency response Wideband Mode Frequency response Wideband Mode Frequency response Narrowband Mode (General Data) Neodymium Magnet Speaker Operational temperature range 45°Cto + 45°C (+41°F to +113°F) Weight, acar hook version 24 g / 0.86 oz Battery (Lithium Polymer) Exchangeable for service (see User manual) Personalization 25 mm / 1.96 in Range – line of sight 180 m / 590 ft Range – in typical office building 55 m / 180 ft Latk time in Mideband Mode 190 to 2 hours Talk time in Mideband Mode 190 to 100 Hours Freakage dimensions (H x W x 0) 940 g / 32.9 oz Package dimensions (H x W x 0) 940 g / 32.9 oz Package dimensions (H x W x 0) 940 g / 32.9 oz	DECT for US				
Base Station Connects to desk phone Headsdet Auto Link to Base Yes, can be activated on the base station Firmware requirement For nevest version please check Sennheiser Updater. Please refer to sennheiser.com/cco/software EHS (Electronic Hook Switch) Microphone Prequency response Wideband Mode Frequency response Wideband Mode Frequency response Narrowband Mode Prequency response Narrowband Mode Frequency response Wideband Mode Frequency response Wideband Mode Frequency response Wideband Mode Frequency response Narrowband Mode Prequency response Narrowband Mode Frequency Response Narrowband Resp	GAP compatible				
Headset Auto Link to Base Firmware requirement For newest version place check Sennheiser Updater. Please refer to sennheiser.com/cco/software Ves (accessory – order EHS adapter separately)	Headset	Connects to base station			
Firmware requirement For newest version please check Sennheiser Updater, Please refer to sennheiser.com/cco/software PLHS (electronic Hook Switch) Yes (accessory – order separately) Yes (Base Station	Connects to desk phone			
EHS (Electronic Hook Switch) Yes (accessory — order EHS adapter separately) Mechanical Hook Lifter HSL 10 (accessory — order separately) Microphone Frequency response Wirdeband Mode Prequency response Narrowband Mode Mute Microphone 300 Hz − 3.5 KHz Speaker Speaker Ype Frequency response Wideband Mode Frequency response Wideband Mode Prequency response Wideband Mode Prequency response Wideband Mode Prequency response Narrowband Mode Prequency response Narrowband Mode Prequency response Narrowband Mode Prequency response Wideband Prequency response Wideband Prequency response Wideband Mode Prepared Wideband Mode Prepared Prepare	Headset Auto Link to Base	Yes, can be activated on the base station			
Microphone 150 Hz − 6.8 KHz Frequency response Wideband Mode Frequency response Wideband Mode Frequency response Narrowband Mode Mute Microphone 150 Hz − 6.8 KHz Speaker 5 Speaker type Neodymium Magnet Speaker Frequency response Wideband Mode Frequency response Wideband Mode Frequency response Narrowband Mode General Data 150 Hz − 6.8 KHz Operational temperature range 45 °C to + 45 °C (+41 °F to +113 °F) Storage temperature range 20 °C to + 70 °C (-4 °F to +158 °F) Weight, ear hook version 24 q/ 0.95 co Ear pad size 9 50 mm / 1.96 in Battery (Lithlum Polymer) Ex khangsable for service (see User manual) Personalization Yes with nameplate on headset Range – line of sight 180 m / 590 ft Range – line of sight 180 m / 590 ft Range – line of sight 180 m / 590 ft Range – line of sight 180 m / 590 ft Talk time in Narrowband Mode Up to 3 hours Stand by time Up to 100 Hours Vera – after 30 minutes 20 minutes Charge time 0 – 50% 20 minutes Charge time 0 – 50% 20 minutes	Firmware requirement	For newest version please check Sennheiser Updater. Please refer to sennheiser.com/cco/software			
Microphone 150 laccessory – order separately) Frequency response Wideband Mode Frequency response Warrowband Mode Mute Microphone 150 Hz − 6.8 KHz Speaker 300 Hz − 3.5 KHz Speaker type Neodymium Magnet Speaker Frequency response Wideband Mode Frequency response Warrowband Mode General Data 150 Hz − 6.8 KHz Operational temperature range +5°C to +45°C (+41°F to +113°F) Voight, ear hook version 24 q/ 0.58 cs Weight, ear hook version 24 q/ 0.58 cs Battery (Lithlum Polymer) Exchangeable for service (see User manual) Personalization Yes with nameplate on headset Range – line of sight 180 m / 590 ft Range – line of sight 180 m / 590 ft Talk time in Narrowband Mode Up to 3 hours Talk time in Narrowband Mode Up to 3 hours Talk time in Narrowband Mode Up to 3 hours Talk time in Narrowband Mode Up to 3 hours Talk time in Narrowband Mode Up to 3 hours Talk time in Narrowband Mode Up to 3 hours Talk time in Narrowband Mode Up to 3 hours Package time 0 – 50% 20 minutes	EHS (Electronic Hook Switch)				
Microphone Frequency response Wideband Mode Frequency response Narrowband Mode Mute Microphone 150 Hz − 6.8 KHz Speaker Neodymlum Magnet Speaker Frequency response Wideband Mode Frequency response Wideband Mode General Data Neodymlum Magnet Speaker Operational temperature range Functional temperature range Weight, ear hook version 24 g / 0.86 oz Weight, ear hook version 24 g / 0.86 oz Weight, headband version 25 g / 0.76 oz Battery (Lithium Polymer) Exchangeable for service (see User manual) Personalization Yes with nameplate on headset Range – In e of sight 180 m / 590 ft Range – In wideband Mode Up to 8 hours Stand by time Up to 8 hours Auto – headset OFF when out of range Charge time 0 – 50%. 20 minutes Charge time 0 – 100%. 16.5 cm x 16 cm x 16 cm Package weight 940 g / 3.29 oz Units in distributor master carton Master carton weight 88 kg / 19.51 lb Safety Se ActiveGard® Protection<	Mechanical Hook Lifter				
Frequency response Wideband Mode Frequency response Narrowband Mode Frequency response Narrowband Mode Frequency response Wideband Mode Frequency response Wideband Mode Frequency response Wideband Mode Frequency response Narrowband Mode Frequency respon	Microphone				
Frequency response Narrowband Mode Mute Microphone 300 Hz = 3.5 kHz Speaker Vyes Yes Speaker type Neodymium Magnet Speaker Frequency response Wideband Mode Frequency response Narrowband Mode General Data 300 Hz = 6.8 kHz General Data 300 Hz = 5.8 kHz Operational temperature range +5 °C to + 45 °C (+41 °F to +113 °F) Storage temperature range +5 °C to + 45 °C (+41 °F to +133 °F) Weight, ear hook version 24 g / 0.86 oz Battery (Lithium Polymer) Exchangeable for service (see User manual) Personalization Yes with nameplate on headset Range – line of sight 180 m / 590 ft Range – in typical office building 55 m / 180 ft Automatic power adjustment Yes (distance between headset and base) Talk time in Narrowband Mode Up to 18 hours Stand by time Up to 18 hours Charge time 0 – 50% 20 minutes Charge time 0 – 50% 20 minutes Package weight 940 g / 32.9 oz Units in distributor master carton 8 Master carton weight 8.5 x 3 x 3 x 3 x m / 14.18 x 14.97 x 14.97 in Sa		150 Hz – 6.8 KHz			
Mute Microphone Yes Speaker Speaker type Neodymium Magnet Speaker Frequency response Wideband Mode Frequency response Narrowband Mode Ceneral Data 150 Hz − 6.8 KHz 300 Hz − 3.5 KHz Operational temperature range Offeneral Data +5 °C to + 45 °C (+41 °F to +113 °F) Storage temperature range Pad visual Pad version 2.0 °C to + 70 °C (-4 °F to +158 °F) Weight, earh nook version 2.4 g / 0.8 eo c 24 g / 0.8 eo c Battery (Lithium Polymer) Exchangeable for service (see User manual) Personalization Yes with nameplate on headset Range – line of sight 180 m / 590 ft Range – line of sight 180 m / 590 ft Range – line of sight 180 m / 590 ft Automatic power adjustment Yes (distance between headset and base) Jut im in Wideband Mode Up to 100 Hours Stand by time Up to 100 Hours Auto – headset OFF when out of range from the complex of					
Speaker Speaker type Neodymium Magnet Speaker Speaker type 150 Hz − 6.8 KHz Frequency response Narrowband Mode 150 Hz − 6.8 KHz General Data 300 Hz − 3.5 KHz Operational temperature range +5 °C to + 45 °C (+41 °F to +113 °F) Storage temperature range +2 °C to + 70 °C (-4 °F to +158 °F) Weight, earh hook version 24 g / 0.86 cg Weight, headband version 50 g / 1.76 cg Ear pad size 0.50 mm / 1.96 in Battery (Lithium Polymer) Exchangeable for service (see User manual) Personalization Yes with nameplate on headset Range – line of sight 180 m / 590 ft Range – line of sight 180 m / 590 ft Range – in typical office building 55 m / 180 ft Yes (distance between headset and base) Up to 12 hours Talk time in Narrowband Mode Up to 12 hours Stand by time Up to 100 Hours Yes → after 30 minutes 20 minutes Charge time 0 – 50% 1hour Charge time 0 – 100% 1hour Package dimensions (H x W x D) 86 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in </th <th></th> <th colspan="4"></th>					
Speaker type	<u>-</u>				
Frequency response Wideband Mode Frequency response Narrowband Mode General Data		Neodymium Magnet Spea	ker		
Frequency response Narrowband Mode General Data Operational temperature range Storage temperature range Weight, ear hook version Weight, headband version So y 1.76 oc Ear pad size Battery (Lithium Polymer) Exchangeable for service (see User manual) Personalization Range – line of sight Range – line of sight Range – line of sight Ves with nameplate on headset Range – line of sight Ves (distance between headset and base) Up to 8 hours Talk time in Narrowband Mode Stand by time Up to 10 Hours Auto – headset OFF when out of range Charge time 0 – 50% Charge time 0 – 50% Charge time 0 – 100% Package dimensions (H x W x D) Package weight Units in distributor master carton Master carton dimensions (H x W x D) Master carton dimensions (H x W x D) Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on egional variant VES "Activation by dip switch VES → Activation by dip switch					
General Data +5 °C to + 45 °C (+41 °F to +113 °F) Operational temperature range +5 °C to + 70 °C (-4 °F to +158 °F) Storage temperature range -20 °C to + 70 °C (-4 °F to +158 °F) Weight, ear hook version 24 g / 0.86 oz Weight, headband version 50 g / 1.76 oz Ear pad size 0.50 mm / 1.96 in Battery (Lithium Polymer) Exchangeable for service (see User manual) Personalization Yes with nameplate on headset Range – in typical office building 55 m / 180 ft Automatic power adjustment Yes (distance between headset and base) Talk time in Nideband Mode Up to 8 hours Talk time in Narrowband Mode Up to 100 Hours Stand by time Up to 100 Hours Auto – headset OFF when out of range Yes * after 30 minutes Charge time 0 – 50% 20 minutes Charge time 0 – 50% 20 minutes Charge time 0 – 50% 1 hour Package dimensions (H x W x D) 16.5 cm x 16 cm x 16 cm Package weight 940 g / 32.9 oz Master carton dimensions (H x W x D) 36 x 38 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in Master carton weight 36 x 38 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in Safety YES ** ActiveGord** Protection YES ** ActiveGord** E					
Storage temperature range Storage temperature range Veight, ear hook version Veight, headband version Storage temperature range Ves mm / 1.96 in Startery (Lithium Polymer) Exchangeable for service (see User manual) Personalization Range - line of sight Storage time of sight Normalization Ves with nameplate on headset Ves (distance between headset and base) Very (distance between headset and ba					
Storage temperature range-20 °C to + 70 °C (-4 °F to +158 °F)Weight, ear hook version24 g / 0.86 ozWeight, headband version50 g / 1.76 ozEar pad sizeØ 50 mm / 1.96 inBattery (Lithium Polymer)Exchangeable for service (see User manual)PersonalizationYes with nameplate on headsetRange – line of sight180 m / 590 ftRange – in typical office building55 m / 180 ftAutomatic power adjustmentYes (distance between headset and base)Talk time in Wideband ModeUp to 8 hoursTalk time in Narrowband ModeUp to 12 hoursStand by timeUp to 100 HoursAuto – headset OFF when out of rangeYes * after 30 minutesCharge time 0 – 50%20 minutesCharge time 0 – 100%1 hourPackage imensions (H x W x D)16.5 cm x 16 cm x 16 cmPackage dimensions (H x W x D)36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 inMaster carton dimensions (H x W x D)36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 inMaster carton weight36 x 38 x 38 cm / 36 x 38 x 38 cm /		 _ +5 °C to + 45 °C (+41 °F t	n +113 °F)		
Weight, ear hook version 24 g / 0.86 oz Weight, headband version 50 g / 1.76 oz Ear pad size ø 50 mm / 1.96 in Battery (Lithium Polymer) Exchangeable for service (see User manual) Personalization Yes with nameplate on headset Range – line of sight 180 m / 590 ft Range – in typical office building 55 m / 180 ft Automatic power adjustment Yes (distance between headset and base) Talk time in Wildeband Mode Up to 8 hours Talk time in Narrowband Mode Up to 12 hours Stand by time Up to 100 Hours Auto – headset OFF when out of range Yes → after 30 minutes Charge time 0 – 50% 20 minutes Charge time 0 – 100% 1 hour Package dimensions (H x W x D) 16.5 cm x 16 cm x 16 cm Package weight 9/40 g / 32.9 oz Units in distributor master carton 8 Master carton dimensions (H x W x D) 36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in Master carton weight 8.85 kg / 19.51 lb Safety Automatic Acoustic Shock Protection YES → Activation by dip switch EU/AUS Limiter depending on regional variant YES → Activation by dip switch					
Weight, headband version 50 g / 1.76 oz Ear pad size Ø 50 mm / 1.96 in Battery (Lithium Polymer) Exchangeable for service (see User manual) Personalization Yes with nameplate on headset Range – line of sight 180 m / 590 ft Range – in typical office building 55 m / 180 ft Automatic power adjustment Yes (distance between headset and base) Talk time in Narrowband Mode Up to 8 hours Talk time in Narrowband Mode Up to 100 Hours Auto – headset OFF when out of range Yes im after 30 minutes Charge time 0 – 50% 20 minutes Charge time 0 – 100% 1 hour Package dimensions (H x W x D) 16.5 cm x 16 cm x 16 cm Package weight 940 g / 32.9 oz Units in distributor master carton 8 Master carton weight 8.85 kg / 19.51 lb Safety Automatic Acoustic Shock Protection YES im Activation by dip switch EU/AUS Limiter depending on regional variant YES im Activation by dip switch					
Ear pad size					
Battery (Lithium Polymer) Exchangeable for service (see User manual) Personalization Yes with nameplate on headset Range – line of sight 180 m / 590 ft Range – lin typical office building 55 m / 180 ft Automatic power adjustment Yes (distance between headset and base) Talk time in Wideband Mode Up to 8 hours Talk time in Narrowband Mode Up to 12 hours Stand by time Up to 100 Hours Auto – headset OFF when out of range Charge time 0 – 50% Charge time 0 – 50% Charge time 0 – 100% Packaging Package dimensions (H x W x D) 16.5 cm x 16 cm x 16 cm y 16 cm x 16 cm y 16 cm x 16 cm y 14.18 x 14.97 x 14.97 in y 18.85 kg / 19.51 lb Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant EVEN with nameplate on headset 180 m / 590 ft 190 makeet carton Accounting the service of the s					
Personalization Yes with nameplate on headset Range – line of sight 180 m / 590 ft Range – in typical office building 55 m / 180 ft Automatic power adjustment Yes (distance between headset and base) Talk time in Narrowband Mode Up to 8 hours Talk time in Narrowband Mode Up to 12 hours Stand by time Up to 100 Hours Auto – headset OFF when out of range Charge time 0 – 50% 20 minutes Charge time 0 – 100% 1 hour Packaging Packaging Package dimensions (H x W x D) 16.5 cm x 16 cm x 16 cm Package weight 940 g / 32.9 oz Units in distributor master carton 8 8 8 5 kg / 19.51 lb Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Yes with nameplate on headset 180 m / 590 ft 180 m / 180 ft 180 m / 590 ft 180 m / 180 ft 180 m					
Range – line of sight180 m / 590 ftRange – in typical office building55 m / 180 ftAutomatic power adjustmentYes (distance between headset and base)Talk time in Wideband ModeUp to 8 hoursTalk time in Narrowband ModeUp to 12 hoursStand by timeUp to 100 HoursAuto – headset OFF when out of rangeYes → after 30 minutesCharge time 0 – 50%20 minutesCharge time 0 – 100%1 hourPackaging16.5 cm x 16 cm x 16 cmPackage dimensions (H x W x D)16.5 cm x 16 cm x 16 cmPackage weight940 g / 32.9 ozUnits in distributor master carton8Master carton dimensions (H x W x D)36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 inMaster carton weight8.85 kg / 19.51 lbSafetyActiveGard®Automatic Acoustic Shock ProtectionYES → ActiveGard®EU/AUS Limiter depending on regional variantYES → Activation by dip switch					
Range - in typical office building55 m / 180 ftAutomatic power adjustmentYes (distance between headset and base)Talk time in Wideband ModeUp to 8 hoursTalk time in Narrowband ModeUp to 12 hoursStand by timeUp to 100 HoursAuto - headset OFF when out of rangeYes → after 30 minutesCharge time 0 - 50%20 minutesCharge time 0 - 100%1 hourPackaging16.5 cm x 16 cm x 16 cmPackage dimensions (H x W x D)16.5 cm x 16 cm x 16 cmPackage weight940 g / 32.9 ozUnits in distributor master carton8Master carton dimensions (H x W x D)36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 inMaster carton weight8.85 kg / 19.51 lbSafetyAutomatic Acoustic Shock ProtectionYES → ActiveGard® ProtectionEU/AUS Limiter depending on regional variantYES → Activation by dip switch					
Automatic power adjustment Talk time in Wideband Mode Talk time in Narrowband Mode Up to 8 hours Up to 12 hours Stand by time Up to 100 Hours Auto – headset OFF when out of range Charge time 0 – 50% Charge time 0 – 100% Packaging Package dimensions (H x W x D) Package weight Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Yes (distance between headset and base) Up to 8 hours Up to 12 hours Ves (distance between headset and base) Up to 8 hours Up to 12 hours 4ter 30 minutes 1 hour 1 hour 1 hour 1 6.5 cm x 16 cm x 16 cm 2 940 g / 32.9 oz 3 6 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in 8 8.85 kg / 19.51 lb Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant YES → Activation by dip switch					
Talk time in Wideband Mode Talk time in Narrowband Mode Up to 12 hours Stand by time Up to 100 Hours Yes → after 30 minutes Charge time 0 – 50% Charge time 0 – 100% Packaging Package dimensions (H x W x D) Package weight Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Up to 12 hours Up to 12 hours Up to 100 Hours 10 Hour 10 Hour 10 Hour 10 Hour 11 Hour 12 Hour 13 Hour 14 Hour 15 Scm x 16 cm x 16 cm 16 Scm x 16 cm x 16 cm 16 Scm x 16 cm x 16 cm 17 Scm x 16 cm x 16 cm 18 Hour 18 Sc x 38 x 38 cm / 14.18 x 14.97 x 14.97 in 18 Hour 19 Hours 10 Hour 10 Hour 10 Hour 10 Hour 11 Hour 12 Hours 13 Hour 14 Hour 15 Hours 16 Hours 16 Hours 17 Hours 18 Hours 18 Hours 18 Hours 18 Hours 18 Hours 19 Hours 19 Hours 10 Hours 10 Hour 10 Hours 10 Hour 10 Hours 10 Hours 10 Hours 11 Hours 11 Hours 12 Hours 13 Hours 14 Hours 15 Hours 16 Hours 17 Hours 18 H					
Talk time in Narrowband Mode Stand by time Auto – headset OFF when out of range Charge time 0 – 50% Charge time 0 – 100% Packaging Package dimensions (H x W x D) Package weight Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Up to 12 hours Up to 100 Hours					
Stand by time Auto - headset OFF when out of range Charge time 0 - 50% Charge time 0 - 100% I hour Packaging Package dimensions (H x W x D) Package weight Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Ves → after 30 minutes 20 minutes 1 hour 1 hour 1 6.5 cm x 16 cm x 16 cm 940 g / 32.9 oz 1 6.5 cm x 16 cm x 16 cm 940 g / 32.9 oz 1 6.5 cm x 16 cm x 16 cm 940 g / 32.9 oz 1 6.5 cm x 16 cm 1 6 cm 1 8 8 8.5 kg / 19.51 lb 940 g / 32.9 oz 1 6.5 cm x 16 cm 1 8 8 8.5 kg / 19.51 lb 940 g / 32.9 oz 1 6.5 cm x 16 cm 940 g / 32.9 oz 1 6.5 cm x 1					
Auto - headset OFF when out of range Charge time 0 - 50% Charge time 0 - 100% Packaging Package dimensions (H x W x D) Package weight Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Yes ➡ after 30 minutes 20 minutes 20 minutes 1 hour 16.5 cm x 16 cm x 16 cm x 16					
Charge time 0 – 100% 1 hour Packaging Package dimensions (H x W x D) Package weight Package weight Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant 20 minutes 1 hour 16.5 cm x 16 cm x 16 cm 940 g / 32.9 oz 16.5 cm x 16 cm x 16 cm 940 g / 32.9 oz 16.5 cm x 16 cm					
Charge time 0 - 100%1 hourPackaging16.5 cm x 16 cm x 16 cmPackage dimensions (H x W x D)16.5 cm x 16 cm x 16 cmPackage weight940 g / 32.9 ozUnits in distributor master carton8Master carton dimensions (H x W x D)36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 inMaster carton weight8.85 kg / 19.51 lbSafetyAutomatic Acoustic Shock ProtectionYES → ActiveGard®EU/AUS Limiter depending on regional variantYES → Activation by dip switch	·				
Package dimensions (H x W x D) Package weight Package weight Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant 16.5 cm x 16 cm x 16 cm 940 g / 32.9 oz 940 g / 32.9 oz 86 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in 88 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in 88 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in 88 x 38 cm / 14.18 x 14.97 x 14.97 in 95 x 36 x 36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in 95 x 36 x 3	-				
Package dimensions (H x W x D) Package weight 940 g / 32.9 oz Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant 16.5 cm x 16 cm x 16 cm 940 g / 32.9 oz 86 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in 88 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in 88 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in 88 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in 88 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in 940 g / 32.9 oz 940 g / 32		<u> </u>			
Package weight 940 g / 32.9 oz Units in distributor master carton 8 Master carton dimensions (H x W x D) 36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in Master carton weight 8.85 kg / 19.51 lb Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant YES → Activation by dip switch		16.5 cm x 16.cm x 16.cm			
Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant 8 36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in 8.85 kg / 19.51 lb YES ActiveGard® YES Activation by dip switch					
Master carton dimensions (H x W x D)36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 inMaster carton weight8.85 kg / 19.51 lbSafetyYES → ActiveGard®ProtectionYES → Activation by dip switchEU/AUS Limiter depending on regional variantYES → Activation by dip switch		•			
Master carton weight 8.85 kg / 19.51 lb Safety YES → ActiveGard® Protection YES → Activation by dip switch EU/AUS Limiter depending on regional variant YES → Activation by dip switch			14 97 x 14 97 in		
Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant YES → ActiveGard® YES → Activation by dip switch					
Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant YES ActiveGard® YES ActiveGard® YES ActiveGard® YES ActiveGard®					
EU/AUS Limiter depending on YES Activation by dip switch regional variant	Automatic Acoustic Shock	YES → ActiveGard [®]			
	EU/AUS Limiter depending on	YES → Activation by dip switch			
	Delivery content				
■ Headset (with name plate for ear hook and distance holder)		nd distance holder)			

- Base Station
- Power supply
- Audio phone cable
- Headband (detachable)
- 1 ear hook adapter with pre-mounted ear hook with leatherette sleeve and earbud size S
- Extra earbuds size M and L
- Name plate holder for headband and name plate instruction
- Printed Quick Guide
- Printed Safety Guide