SENNHEISER SDW 5036 Specs

Headset Features Hearing Protection, Noise Cancellation

Microphone

Microphone Design	Boom
Microphone Frequency Response	150 Hz to 3.5 kHz (Narrowband) 100 Hz to 7.5 kHz (Wideband) 100 Hz to 11 kHz (Super Wideband)

Speaker

Earpiece Design	On-Ear
Listening Mode	Monaural
Speaker Frequency Response	50 Hz to 11.5 kHz (Super Wideband) 50 Hz to 7.5 kHz (High-Density Wideband) 50 Hz to 7.5 kHz (Wideband) 150 Hz to 3.5 kHz (Narrowband) 20 Hz to 20 kHz (Fullband)
Maximum Sound Pressure Level (SPL)	118 dB

Connectivity

Wireless Range	590' / 179.8 m
Wireless Technology	DECT
Host Connection	1 x USB Type-A

Power

Recharge Time	1.5 Hours
Standby Time	44 Hours
Talk Time	9 to 14 Hours

Environmental

Operating Temperature	41 to 113°F / 5 to 45°C
Storage Temperature	-4 to 158°F / -20 to 70°C

General

Wearing Style	Over-the-Head
Encryption Bit Depth	128-Bit

Physical

Ear Pad Size	2.1" / 54.5 mm
Weight	3.5 oz / 100 g (Headset)