

Specifications

Frequency Range (-10dB)	45 Hz - 19.5 kHz
Coverage Pattern (-6 dB)	Horizontal: 60; Vertical: 60
System Input Power Rating	Passive: 1500 W Continuous (IEC / 100 hour) Active: LF: 1500 W Continuous (IEC / 100 hour) HF: 100 W Continuous (IEC / 100 hour)
Maximum SPL (1m)	138 dB (Preset: VTX M22 FR)
System Latency ³	3.33ms
System Amplification	Crown Audio I-Tech HD
Nominal Impedance	Passive: 4 ohms Active LF: 4 ohms Active HF: 8 ohms
LF Driver	2 x 2262H, 304 mm (12 in) diameter, dual 76 mm (3 in) diameter voice coil, NDD®, Direct Cooled™
HF Driver	1 x D2430H, D2 dual diaphragm, dual 76mm (3 in) diameter voice coil
Monitor Angle	30 degrees
Enclosure	mm, 11-ply Finnish birch plywood
Grille	Powder Coated 14 gauge hex-perforated steel with acoustically-transparent black cloth backing
Input Connectors	Passive: Neutrik® Speakon® NL-4 (4x): Selectable: Pins 1 ± or Pins 2 ± Active: Neutrik® Speakon® NL-4 (4x): Pins 1 ± (LF) Pins 2 ± (HF)
Dimensions (H x W x D)	380 mm x 671 mm x 555 mm (15 in x 26.4 in x 21.8 in)
Net Weight (each)	27 kg (60 lbs)