99 Washington Street Melrose, MA 02176 Phone 781-665-1400 Toll Free 1-800-517-8431





Fluke 1000FLT Fluorescent Light Tester

Take the trial and error out of fluorescent light testing

Technical Data

The most complete lamp tester helps save you time, reduce costs

The Fluke 1000FLT allows you to perform 5 tests with 1 compact tool. If your job requires keeping large numbers of fluorescent lights shining, the Fluke 1000FLT is an indispensable tool. This tester is a real time and money saver.

Save time, reduce costs

The Fluke 1000FLT offers 5 essential lighting tests:

- Lamp test: test bulb without removing from fixture
- Ballast test: easily determine if ballast is working
- Non-contact voltage: quickly check for voltage presence
- Pin continuity test: tests if filaments have continuity
- Ballast-type test: determine if ballast is electronic or magnetic without taking fixture apart—identify energy wasting ballasts Other key benefits:
- Survives on-the-job handling: drop-tested to survive from a six foot (two meter) ladder
- Easy to use: bright indicator light plus audible alert
- Rugged: backed with a three-year warranty







Technical specifications

Test specifications	
Lamp Test Max Output	3000 V peak-peak
Ballast Test	20 kHz
Ballast Type Discriminator	≤3 m (10 ft) distance
Pin Continuity Test	$< 1 \text{ k}\Omega$
NCV (VoltAlert TM)	85 to 277 V ac
NCV (VOITAIEIT)	45 to 67 Hz
	≤10 cm (4 in) distance
Environmental specifications	
Temperature	Operating -10 °C to +50 °C (14 °F to +122 °F) Storage -40 °C to +60 °C (-40 °F to +140 °F)
Relative Humidity	85 % maximum
Safety specifications	
Safety rating	IEC 61010-1, pollution degree 2
Mechanical & General Specifications	
Size	21.5 cm x 3.0 cm x 6.5 cm (8.5 x 1.2 x 2.6 in)
Weight	0.37 kg (0.80 lb.)
Battery type	4 x AA alkaline IEC LR6
Battery life	40 hours
Auto Power Off	20 minutes after non-use
Low Battery Indicator	Power button light blinks when power is low (typi-
,	cally 85% of capacity depleted)
Operating altitude	< 2000 m
Electromagnetic	EN 61326-1: Portable
Environment	
Electromagnetic Compatibility	GE CISPR 11: Group 2, Class A Group 2 contains all ISM RF equipment in which radio-frequency energy in the frequency range 9 kHz to 400 GHz is intentionally generated and used or only used, in the form of electromagnetic radiation, inductive and/or capacitive coupling, for the treat- ment of material or inspection/analysis purposes Class A equipment is suitable for use in non- domestic locations and/or directly connected to a low-voltage power supply network. US FCC Part 15 Subpart B – exempt as test equipment per clause 15.103
	Korea only Class A Equipment (Industrial Broadcasting & Communication Equipment) 1 This product meets requirements for industrial (Class A) electromagnetic wave equipment and the seller or user should take notice of it. This equipment is intended for use in business environments and not to be used in homes.
Resistance to impact	2 meter drop
Warranty	3 years

Ordering information

Fluke-1000FLT Fluorescent Light Tester

Includes: 1000FLT Fluorescent Light Tester, quick reference guide, four AA alkaline batteries, H1000 Holster, warranty card (3 year warranty)

> Fluke. Keeping your world up and running.®

©2014 Fluke Corporation. Specifications subject to change without notice. Printed in U.S.A. 6/2014 6002970A_EN

Modification of this document is not permitted without written permission from Fluke Corporation.