

# PT-RZ790 Series

1-Chip DLP™ Projectors

AVAILABLE FROM SEPTEMBER 2020

## Compact 1-Chip DLP™ Laser Projectors Bring High Brightness and Simple Flexibility to Exhibition Spaces



Black Models



White Models



PT-RZ790 Series				
	PT-RZ790	PT-RZ790L	PT-RZ690	PT-RZ690L
Light Output	7,000 lm*1/7,200 lm (Center)*2		6,000 lm*1/6,200 lm (Center)*2	
Resolution	WUXGA			
Lens	Lens supplied	Without lens	Lens supplied	Without lens

### • **Bright, Color-Rich Images in Any Environment**

The PT-RZ790 Series delivers the brightness, resolution, and color that designers need to enhance exhibits with bright, bold, and vivid pictures. SOLID SHINE Laser and Quartet Color Harmonizer enhance color-depth and white-balance accuracy for arrestingly realistic pictures even in well-lit spaces.

### • **Light, Quiet, Compact Projectors are Easy to Install**

Projectors support our 1-Chip DLP™ lenses and 4K signal input\*3 via HDMI® and DIGITAL LINK, adapting to your space with 23.2 kg\*4 body and 36 dB operation in Normal Mode. Smart Projector Control app enhances efficiency with On/Off function, lens adjustment, touchscreen OSD navigation, and projection auto-focusing using your smartphone camera\*5.

### • **Proven SOLID SHINE Laser Reliability**

Hermetically sealed DMD block, shielded laser drive, and new filterless cooling system eliminate the hassle of maintenance for 20,000 hours\*6 of continuous projection, while brightness ramp and color uniformity remain linear. For extra insurance, Backup Input\*7 switches to a failback if primary video is interrupted.

\*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2012 international standards. Value is average of all products when shipped. \*2 Average light-output value of all shipped products measured at center of screen in NORMAL Mode. \*3 4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection. Supported terminals: DIGITAL LINK/HDMI®. \*4 Including standard lens. \*5 Projector auto-focus may not be supported on some mobile devices. \*6 Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast Contents, NORMAL Mode, Dynamic Contrast [ON], temperature 35 °C (95 °F), elevation 700 m (2,297 ft) with 0.15 mg/m³ of airborne particulate matter. Estimated time until brightness decreases to 50 % will vary depending on environment and usage conditions. Parts other than the light source may require replacement before 20,000 hours, and checkup is recommended around this time. \*7 Combination of primary/backup input terminals is fixed. Backup Input function enabled when input signal to primary/backup terminals is the same.

## Specifications (Tentative)

Model	With supplied lens	PT-RZ790	PT-RZ690
	Without lens	PT-RZ790L	PT-RZ690L
Projector type		1-Chip DLP™ projector	
DLP™ chip	Panel size	17.0 mm (0.67 in) diagonal (16:10 aspect ratio)	
	Display method	DLP™ chip x 1, DLP™ projection system	
	Number of pixels	2,304,000 (1920 x 1200 pixels)	
Light source		Laser diodes	
Light output		7,000 lm*/7,200 lm (Center)*2	6,000 lm*/6,200 lm (Center)*2
Time until light output declines to 50 %*3		20,000 hours (NORMAL)/24,000 hours (ECO)	
Resolution		1920 x 1200 pixels	
Contrast ratio*4		10,000:1 (Full On/Full Off, Dynamic Contrast Mode: ON)	
Screen size [diagonal]		1.27–15.24 m (50–600 in), 1.27–5.08 m (50–200 in) with ET-DLE055, 2.54–8.89 m (100–350 in) with ET-DLE035, 2.54–10.16 m (100–400 in) with ET-DLE020, 16:10 aspect ratio	
Center-to-corner zone ratio*1		90 %	
Lens		PT-RZ790: Powered zoom (throw ratio 1.71–2.41:1), powered focus F 1.7–1.9, f 25.6–35.7 mm PT-RZ790L: Optional powered zoom/focus lenses	PT-RZ690: Powered zoom (throw ratio 1.71–2.41:1), powered focus F 1.7–1.9, f 25.6–35.7 mm PT-RZ690L: Optional powered zoom/focus lenses
Lens shift*4 (From the origin point of the lens mounter)	Vertical	+50 %, -16 % (+40 %, -16 % with ET-DLE060) (powered)	
	Horizontal	+30 %, -10 % (+10 %, -20 % with ET-DLE020, +19 %, -10 % with ET-DLE060, +28 %, -10 % with ET-DLE105/ET-DLE085) (powered)	
Keystone correction range		Vertical: ±40 ° (±5 ° with ET-DLE020, ±16 ° with ET-DLE060, ±22 ° with ET-DLE105/ET-DLE085/ET-DLE055, +5 ° with ET-DLE035), Horizontal: ±15 ° (±10 ° with ET-DLE060) (cannot be operated with ET-DLE035/ET-DLE020)	
Keystone correction range with optional ET-UK20 Upgrade Kit		Vertical: ±45 ° (±16 ° with ET-DLE060, ±40 ° with ET-DLE150/ET-DLE250/ET-DLE170, ±22 ° with ET-DLE105/ET-DLE085/ET-DLE055), Horizontal: ±40 ° (±10 ° with ET-DLE060, ±15 ° with ET-DLE105/ET-DLE085/ET-DLE055) When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of 55 °.	
Installation		Ceiling/floor, front/rear, free 360-degree installation	
Terminals	SDI IN	BNC x 1: 3G/HD/SD-SDI input	
	HDMI® IN	HDMI 19-pin x 1 (Compatible with HDCP 2.2, Deep Color, 4K signal input*5)	
	DVI-D IN	DVI-D 24-pin x 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only)	
	RGB 1 IN	RGB x 1 (BNC x 5): RGB/YPbPr/YCbCr/Y/VIDEO	
	RGB 2 IN	D-sub HD 15-pin (female) x 1: RGB/YPbPr/YCbCr	
	SERIAL/MULTI PROJECTOR SYNC IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)	
	SERIAL/MULTI PROJECTOR SYNC OUT	D-sub 9-pin (male) x 1 for link control	
	REMOTE 1 IN	M3 x 1 for wired remote control	
	REMOTE 1 OUT	M3 x 1 for link control (for wired remote control)	
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)	
	DIGITAL LINK	RJ-45 x 1 for network and DIGITAL LINK connections (HDBase™ compliant), PLink™ (Class 2) compatible, 100Base-TX, Art-Net compatible, HDCP 2.2 compatible, Deep Color compatible, 4K signal input*5	
	LAN	RJ-45 x 1 for network connection, PLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible	
	Power supply		AC 100–240 V, 50/60 Hz
Power consumption		TBD	
Cabinet materials		Molded plastic	
Operation noise*1		36 dB	
Dimensions (W x H x D)		PT-RZ790: 498 x 200*6 x 581 mm (19 19/32" x 7 7/8" x 22 7/8") (with supplied lens)	PT-RZ690: 498 x 200*6 x 581 mm (19 19/32" x 7 7/8" x 22 7/8") (with supplied lens)
		PT-RZ790L: 498 x 200*6 x 538 mm (19 19/32" x 7 7/8" x 21 3/16") (without lens)	PT-RZ690L: 498 x 200*6 x 538 mm (19 19/32" x 7 7/8" x 21 3/16") (without lens)
Weight*7		PT-RZ790: Approx. 23.2 kg (51.1 lbs) (with supplied lens)	PT-RZ690: Approx. 23.2 kg (51.1 lbs) (with supplied lens)
		PT-RZ790L: Approx. 22.4 kg (49.4 lbs) (without lens)	PT-RZ690L: Approx. 22.4 kg (49.4 lbs) (without lens)
Operating environment		TBD	
Applicable software		Logo Transfer Software, Multi Monitoring & Control Software, Geometry Manager Pro (ET-UK20 Upgrade Kit, ET-CUK10 Auto Screen Adjustment Kit), Smart Projector Control for iOS/Android™	

\*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2012 international standards. Value is average of all products when shipped. \*2 Average light-output value of all shipped products measured at center of screen in NORMAL Mode. \*3 Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast contents, NORMAL Mode, Dynamic Contrast [ON], under conditions with 35 °C (95 °F), 700 m (2,297 ft) above sea level, and 0.15 mg/m<sup>3</sup> of particulate matter. Estimated time until light output declines to 50 % varies depending on environment. \*4 Lens shift is not supported on the ET-DLE055, and the optical axis is fixed with the ET-DLE035. \*5 4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection. Supported terminals: DIGITAL LINK/HDMI®. \*6 Excluding legs. \*7 Average value. May differ depending on the actual unit.

## Optional Accessories

- Fixed-Focus Lens**  
 ET-DLE030 (0.380:1) / ET-DLE035 (0.380:1) / ET-DLE055 (0.785:1)
- Zoom Lens**  
 ET-DLE020 (0.280–0.299:1) / ET-DLE060 (0.600–0.801:1) /  
 ET-DLE085 (0.782–0.977:1) / ET-DLE105 (0.978–1.32:1) /  
 ET-DLE150 (1.30–1.89:1) / ET-DLE170\* (1.71–2.41:1) /  
 ET-DLE250 (2.27–3.62:1) / ET-DLE350 (3.58–5.45:1) /  
 ET-DLE450 (5.36–8.58:1)  
*\* The ET-DLE170 is equivalent of supplied lens. The availability of the ET-DLE170 varies depending on the country.*
- Ceiling Mount Bracket**  
 ET-PKD130H (6-axis, for high ceiling)  
 ET-PKD120H (for high ceiling)  
 ET-PKD120S (for low ceiling)  
*Note: Use ET-PKD120H, ET-PKD120S, and ET-PKD130H in combination with ET-PKD130B. ET-PKD130H is recommended when used with ET-DLE030/ET-DLE035.*
- Projector Mount Bracket**  
 ET-PKD130B
- DIGITAL LINK Switcher**  
 ET-YFB200G  
*Note: ET-YFB200G is not compatible with 4K signals.*
- Digital Interface Box**  
 ET-YFB100G  
*Note: ET-YFB100G is not compatible with 4K signals.*
- Geometry Manager Pro Software Upgrade Kit**  
 ET-UK20
- Auto Screen Adjustment Upgrade Kit**  
 ET-CUK10/ET-CUK10P
- Early Warning Software**  
 ET-SWA100 Series  
*Note: Part number suffix may differ depending on the license type.  
 \* Multi Monitoring & Control Software Ver. 2.0 or later is required. Please download from the following website: [www.panasonic.net/cns/projector/download/application/](http://www.panasonic.net/cns/projector/download/application/)*

# Panasonic®

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Product availability may vary by country or region. This product may be subject to export control regulations. DLP, DLP logo and DLP Medallion logo are trademarks or registered trademarks of Texas Instruments. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries. Trademark PLink is a trademark applied for trademark rights in Japan, the United States of America and other countries and areas. Android is a trademark or registered trademark of Google LLC. IOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license. SOLID SHINE is a trademark of Panasonic Corporation. All other trademarks are the property of their respective trademark owners. © 2020 Panasonic Corporation. All rights reserved.



For more information about Panasonic projectors, please visit:  
 Projector Global Website – [panasonic.net/cns/projector](http://panasonic.net/cns/projector)  
 Facebook – [www.facebook.com/panasonicprojectoranddisplay](https://www.facebook.com/panasonicprojectoranddisplay)  
 YouTube – [www.youtube.com/user/PanasonicProjector](https://www.youtube.com/user/PanasonicProjector)

All information included here is valid as of February 2020.

PT-RZ790PRE1 Printed in Japan.