



APC Easy Rack PDU, Basic, 0U, 1 Phase, 7.4kW, 230V, 32A, 20 x C13 and 4 x C19 outlets, IEC60309 2P+E inlet

EPDU1132B

Overview

Lead Time	Usually in Stock

Main

Colour	Black
Pdu Type	Basic
Cable Length	3.00 m
Number Of Cables	1
Provided Equipment	Installation guide Toolless mounting kit Vertical mounting brackets

Complementary

Main Input Voltage	200 V
	208 V
	230 V
Height	117.5 cm
Width	6.2 cm
Main Output Voltage	230 V
Depth	4.44 cm
Net Weight	3.58 kg
Mounting Location	Side
Mounting Preference	No preference
Input Connection Type	IEC 60309 32 A 2P + E
Mounting Mode	Rack-mounted
Number Of Rack Unit	0U
Mounting Position	Vertical
Input Current Limits	32 A
Load Capacity	7360 VA
Network Frequency	50/60 Hz
Number Of Power Socket Outlets	20 IEC 60320 C13
	4 IEC 60320 C19

Environment

Product Certifications	CE
	TÜV

Ambient Air Temperature For Operation	045 °C
Relative Humidity	595 %
Operating Altitude	010000 ft
Ambient Air Temperature For Storage	-2565 °C
Storage Relative Humidity	595 %
Storage Altitude	0.009144.00 m

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	132 cm
Package 1 Width	16 cm
Package 1 Length	11 cm
Package 1 Weight	4.351 kg

Contractual warranty

Warranty 1 year repair or replace



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more about Green Premium >





Transparency RoHS/REACh

Well-being performance

	Reach Free Of Svhc	
②	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information