



# DMInteract®

## STAGE LIGHTS DATASHEET

Explore DMInteract Stage Lights - Professional Lighting Solutions for Every Performance



# DMInteract® **BEAM LIGHTS**

High-Precision Beam Lights - Illuminate Your  
Stage with Power and Focus

## DM-BL600W

### 11 Colors with DMX 16 Channels 470W



- **Voltage:** AC100-240V 50/60Hz
- **Power:** 600W
- **Light Source:** 440W/470W Yodn Lamp
- **Channels:** DMX 16 Channels
- **Color Wheel:** One color wheel, 11 colors
- **Gobo:** One static gobo wheel, 12 gobos + open
- **Prism:** Two rotating prisms, one 8 facet prism and one 16 prism
- **Frost:** Gradually frost, wash angle 5-30 degrees
- **Lens:** Glass optic lens, linear zoom 0-20 degrees
- **Control Mode:** DMX512, Sound, Auto, Master Slave

## DM-BL250W

### 13 Colors with Rainbow Effect, 250W



- **Voltage:** AC100-240V 50/60Hz
- **Power:** 300W
- **Light Source:** 250w Lamp
- **Blast/Channel:** Electronic Ballast / DMX 16 Channels
- **Color Wheel:** One color wheel, 13 colors + blank, with a rainbow effect
- **Gobo:** One static gobo wheel, 14 gobos + open
- **Prism:** Two rotating prisms, one 16 facet prism and one 8+16 prism
- **Frost:** Gradually frost, wash angle 5-30 degrees
- **Lens:** Glass optic lens, linear zoom 0-20 degrees
- **Control Mode:** Pan 540 degrees, 8/16 bit resolution, Tilt 270 degrees, 8/16 bit resolution

## DM-BL230W

### 14 Colors 230W Beam Stage Light



- **Voltage:** AC100-240V 50/60Hz
- **Power:** 300W
- **Light Source:** 250w Lamp
- **Blast/Channel:** Electronic Ballast / DMX 16 Channels
- **Color Wheel:** One color wheel, 14 colors + blank
- **Gobo:** One static gobo wheel, 17 gobos + open
- **Prism:** Two rotating prisms, one 8/16 facet prism
- **Frost:** Gradually frost, wash angle 5-30 degrees
- **Lens:** Glass optic lens, linear zoom 0-20 degrees
- **Control Mode:** Pan 540 degrees, 8/16 bit resolution; Tilt 270 degrees, 8/16 bit resolution



## DM-BL330W

### 3in1 330W Beam Stage Light



- **Voltage:** AC100-240V 50/60Hz
- **Power:** 330W
- **Light Source:** 330W Osram Lamp
- **Channels:** DMX 16 Channels
- **Color Wheel:** One color wheel, 14 colors + blank, with rainbow effect
- **Gobo:** One static gobo wheel, 13 gobos + open
- **Prism:** Two rotating prisms, one 8 facet prism and one 16 prism
- **Frost:** Gradually frost, wash angle 5-30 degrees
- **Lens:** Glass optic lens, linear zoom 0-20 degrees
- **Control Mode:** Pan 540 degree, 8/16 bit resolution, colors + blankTilt 270 degree, 8/16 bit resolution

## DM-BL260W

### 3in1 260W Beam Stage Light



- **Voltage:** AC100-240V 50/60Hz
- **Power:** 300W
- **Light Source:** 260w Lamp
- **Blast/Channel:** Electronic Ballast / DMX 17 Channels
- **Color Wheel:** One color wheel, 13 colors + blank, with a rainbow effect
- **Gobo:** One static gobo wheel, 14 gobos + open
- **Prism:** Two rotating prisms, one 16 facet prism and one 8+16 prism
- **Frost:** Gradually frost, wash angle 5-30 degrees
- **Lens:** Glass optic lens, linear zoom 0-20 degrees
- **Control Mode:** Pan 540 degrees, 8/16 bit resolution; Tilt 270 degrees, 8/16 bit resolution

## DM-BL7R

### 230W 3in1 Beam Stage Light




- **Voltage:** AC100-240V 50/60Hz
- **Power:** 230W
- **Light Source:** 230w Lamp
- **Blast/Channel:** Electronic Ballast / DMX 16/24 Channels
- **Color Wheel:** One static gobo wheel, 16 gobos + open; One rotating gobo wheel, 7 gobos + open
- **Gobo:** One static gobo wheel, 17 gobos + open
- **Prism:** Two rotating prisms, one 8/16 facet prism
- **Frost:** Gradually frost, wash angle 5-30 degrees
- **Lens:** Glass optic lens, linear zoom 0-20 degrees
- **Control Mode:** Pan 540 degree, 8/16 bit resolution, Tilt 270 degree, 8/16 bit resolution

## DM-BL17R

### 3in1 330W Beam Stage Light



- **Voltage:** AC100-240V 50/60Hz
- **Power:** 500W
- **Light Source:** 350W Osram 17R for bright output
- **Channels:** DMX 16/24 Channels
- **Color Wheel:** One color wheel, 13 colors
- **Gobo:** One static gobo wheel, 13 gobos + open; One rotating gobo wheel, 9 gobos + open
- **Prism:** Two rotating prisms, one 8-facet prism and one linear 6-prism
- **Frost:** Gradually frost, wash angle 5-30 degrees
- **Lens:** Glass optic lens, linear zoom 0-20 degrees
- **Control Mode:** Pan 540 degree, 8/16 bit resolution, colors + blankTilt 270 degree, 8/16 bit resolution





# DMInteract® **MOVING HEAD LIGHTS**

High-Precision Moving Head Lights - Illuminate  
Your Stage with Power and Focus

## DM-MHL380

### 108 Pcs RGB LED Wash Moving Head Stage Light



- **Voltage:** AC100-240V 50/60Hz
- **Power:** 380W
- **Light Source/Power:** LED 108\* / 3W RGBW
- **Frequency:** 50/60Hz
- **Channels:** 14/18 Channel
- **Flare Angle:** 25°
- **Scanning Angle:** 540° (lvel), 540° (vertical)
- **Operation Mode:** Master-slave/Sound/Auto
- **Dimmer & Strobe:** A highly electronic dimmer strobe can reach 1-20t/s
- **Color:** RGB color mixture evenly, system, and rainbow effect (additive white)

## DM-MHL710

### 4 in 1 CREELED Moving Head Stage Light



- **Voltage:** AC100-240V 50/60Hz
- **Power:** 120W
- **Light Source/Power:** 7 pcs 10W 4-in-1 CREE LEDs
- **Frequency:** 50/60Hz
- **Channels:** 15 Channel
- **X-Y Angle:** 540° / 270° ,controllable speed
- **Optical Angle:** 8°
- **Electronic:** Stroboscopic band pulse and random effect
- **Fox:** Subminiature, lightweight design
- **Smooth-electronic dimming:** 0-100%

## DM-MHL100W

### 100W Mini Bee Beam Moving Head Stage Light



- **Voltage:** AC100-240V 50/60Hz
- **Power:** 100W
- **Light Source/Power:** 6pcs \*15W, RGBW 4in 1 LED chip
- **Color rotation system:** RGBW 4in 1 rotation, Marco color system
- **Strobe:** 1-30 times/ second electronic strobe and random strobe
- **Channel:** Standard Channel-11. Extend Channel-17
- **X-Y Angle:** 540° /270° , controllable speed
- **Pan/Tilt:** 540° /1.5 seconds 180°/0.5 seconds
- **Control Mode:** DMX512, RDM, Stand-alone mode, Voice Control mode; Master- Slave mode, Wireless DMX512.



## DM-MHL140

### 3x3 LED Spider Moving Head Stage Light



- **Voltage:** AC100-240V 50/60Hz
- **Power Consumption:** 140W
- **Source:** 9\* 10-Watt RGBW Cree LEDs
- **3 Operational modes:** Sound, DMX 512, master/slave, and Auto
- **DMX Channel:** 15/45CH
- **Electronic Dimming:** 0-100%
- **Includes:** Exciting sound-active built-in programs
- **Pan:** 0-540 degrees
- **Lifetime:** Extremely Long Life (20,000 hr. rated)
- **Beam angle:** 5 Degrees

## DM-MHL9-10W

### IP67 9 LEDs Matrix Limitless Moving Head Stage Light



- **Voltage:** AC 100-240V 50/60V
- **Power:** 120W
- **Light Source:** 9 pcs 10W RGBW 4-in-1 LEDs
- **Channels:** 16/47 DMX channels selectable
- **Beam Angle:** 6.5°
- **Pan/Tilt:** 360° limitless rotation 1000Hz refresh rate
- **Sound is Controlled:** Via a built-in microphone.
- **Adjustable:** Sound Sensitivity
- **Function:** Beam effect, master/slave, Sound, DMX512
- **Control:** Art Net, Kling Net Protocol

## DM-MHL9-10W

### 120W IP67 9 LEDs Matrix Moving Head Stage Light



- **Voltage:** AC100-240V 50/60Hz
- **Power:** 120W
- **Light Source/Power:** 9 pcs 10W RGBW 4-in-1 LEDs
- **Channel:** Standard Channel-11. Extend Channel-17
- **X-Y Angle:** 540° / 270° , controllable speed
- **Pan/Tilt:** 360° limitless rotation 1000Hz refresh rate
- **Sound is Controlled:** Via a built-in microphone.
- **Adjustable:** Sound Sensitivity
- **Function:** Beam effect, master/slave, Sound, DMX512
- **Control:** Art Net, Kling Net Protocol



## DM-MHL150W

### 7x12W 4IN1 Mini Bee Eye Moving Head Stage Light



- **Voltage:** AC100-240V, 50-60Hz
- **Power consumption:** 150W
- **Source:** 7 pcs 12W RGBW 4-in-1 LEDs
- **Control Mode:** DMX512, Master-Slave Auto, Sound
- **Beam angle:** 4-45°
- **Strobe:** 0-25 Hz
- **Color:** RGBW infinite color mixture system
- **Channel:** 18CH
- **Working Temperature:** -25° C-40° C
- **Working Lifetime:** 50,000 hours
- **Pan/Tilt:** 540°, 270°
- **IP rate:** IP20 (indoor use only)

## DM-MHL300W

### LED Light Strip Adjustable Moving Head Stage Light



- **Voltage:** AC 100-240V 50/60V
- **Power:** 300W
- **Light Source:** 25 pcs \* 10W RGBW 4-in-1 LEDs
- **Channels:** 16/37/112 DMX channels selectable
- **Beam Angle:** 6.5°
- **Pan/Tilt:** 360° limitless rotation 1000Hz refresh rate
- **Sound is Controlled:** Via a built-in microphone.
- **Adjustable:** Sound Sensitivity
- **Function:** Beam effect, master/slave, Sound, DMX512
- **Control:** Art Net, Kling Net Protocol

## DM-MHL90W

### 90W Luxeon LED With 7 Colors M-Head Stage Light



- **Voltage:** AC110- 220V 50- 60Hz
- **Power:** 100W
- **Channel:** 15 DMX
- **Source:** 1 PCS 90W Luxeon LED, White
- **Control Mode:** DMX512, Master-Slave, Auto, Sound
- **Gobo:** 8 rotating gobos + white + vibrating gobo + 7 fixed gobos running
- **Color:** 7 colors + white + color running
- **Focus:** Auto
- **Prism:** Triple prism
- **Size:** 32x30x39.5cm

## DM-MHL36

### 36\*10W 6in1 RGBW LED Zoom Moving Head Stage Light



- **Voltage:** AC100-240V, 50-60Hz
- **Power:** 430W
- **Source:** 36\* 10W RGBW 4 in 1/5 in 1/6 in 1 LEDs
- **Mode:** Auto, Sound, DMX512, Master-slave
- **Channel:** 16CH
- **Strobe:** from fast to slow, adjusting.
- **Electronic dimmer:** 0-100%, Zoom function
- **Pan:** 540° .Tilt 270° Pan/Tilt speed adjusted
- **Display:** LCD
- **Size:** 420x330x460mm





# DMInteract® **WALL LIGHTS**

High-Precision Wall Lights—Illuminate Your  
Stage with Power and Focus



## DM-WL126

### 126W 36Pcs LED Gold Matrix Wall Stage Light



- **Power Voltage:** AC100-240V, 50/60Hz
- **Power Consumption:** 126W
- **Light Sources:** 36x3W warm white LED
- **DMX Channel:** 3/4/36 Channel
- **Firmware Upgrade:** Update via DMX link
- **Data In/Out:** 3-pin & 5-pin XLRs, RJ45
- **Design:** Slim and compact design with excellent thermal control
- **LEDs Controlled:** Pixel by Pixel, delivering versatile effects.
- **Smooth:** 0-100% linear dimmer, strobe speeds, Electrical and Physical
- **Control Modes:** DMX, ArtNet, Master/Slave, Sound Active
- **Dimension:** 500x500x89mm

## DM-WL800

### 800W 3in1 LED Matrix Wall Stage Light



- **Voltage:** AC1 110-240V/50-60Hz
- **Power:** 800W
- **Source:** Lumi-Engine 30Wx25pcs LED 3 in 1
- **Dimmer:** 0-100%
- **Strobe:** 0-27 Hz
- **Control Channel:** 8CH/80CH
- **Control Mode:** DMX512, Master-Slave, Sound, Auto
- **Display:** Digital Display Screen
- **Carton Size:** 66x65x23cm

## DM-WL500

### 500W/550W 180Pcs RGBW 4in1 LED Wall Stage Light



- **Voltage:** AC100-240V 50/60Hz
- **Power:** 500W/550W
- **Type:** B180PCSx9W RGB3IN1
- **LED Life:** About 50000 hours
- **Beam Angle:** 8°, 15°, 25°, 35°, 45°, 60°
- **Effect:** Dimmer 0~100%
- **Stroboscopic:** 0-20 Hz
- **Channel:** (STAGE mode) or 3 (HSV mode)
- **Control mode:** DMX512, Master-slave Mode
- **Shell material:** Aluminum alloy

## DM-WL1200

### 1200W 120Pcs RGBW 4 in 1 LED Wall Stage Light



- **Input Voltage:** AC90-240V 50/60Hz
- **Power:** 1,200 W
- **Light Source Quantity:** 10W 120 pcs (RGBW 4 in 1)
- **Light Life:** 6-10 hours
- **Dimmer:** 0-100%
- **Stroboscopic:** 1-20 times/sec
- **Lens Angle:** 15°, 25°, 35°, 45° (optional)
- **Effect Distance:** 60m
- **Show Board:** Digital/LCD
- **Mode:** DMX512, 3-core interface, master-slave, Auto, Sound
- **DMX Channel:** 4/8/12CH
- **Cooling System:** Natural Convection Heat Transfer

## DM-WL24

### 24x3W Colorful LED Washer Wall Stage Light



- **Input Voltage:** AC180V-256V
- **Power Consumption:** 24W/72W
- **Source:** 3W LED 24pcs Colorful
- **Project Distance:** 20m
- **Source Life:** 50000 Hours
- **Control System:** DMX 512 Control
- **DMX Channel:** 7 Channels
- **Operating Voltage:** 18VDC 320mA  $\pm$  5%
- **Protection Rating:** IP65
- **Operating Temperature Range:** -18° C to +40° C (-0.4° F to 104° F)
- **Tilt Rotary Angle:** 175° Housing: Aluminum only
- **Size:** L100xW7.6xH10cm



# DMInteract® **COB LIGHTS**

High-Precision COB Lights—Illuminate Your  
Stage with Power and Focus



## DM-COB450

### 100W 4 x 100 Indoor Blinder COB Stage Light



- **LED:** 4 pcs x 100W COB LED
- **LED light time:** over 50000 hours
- **Voltage:** AC 100V-240V 50-60Hz
- **Power consumption:** 400W
- **Beam angle:** 30 degrees
- **Dimmer:** 0-100% linear adjustable
- **Strobe:** Variable speed (1-30 Hz)
- **Color effect feature:** Individual control of the effect
- **Control Mode:** DMX512 , Master/Slave, auto Sound alone, Sound active
- **DMX Channel:** 2/4/8 CH

## DM-COB400

### 4500W 4 x 100 Waterproof Blinder COB Stage Light



- **Lamp Source:** 4 pcs 100W 2800K / 3200K 6500K / 3200+6500K COB LED
- **Power:** 400W
- **Led Control:** FULL
- **DMX Channels:** 2/6 CHS
- **Lens:** 45 degree
- **Color:** 2800K / 3200K 6500K / 3200+6500K
- **Effect:** Audience Light
- **Display:** LED
- **IP grade:** IP65

## DM-COB250

### 100W 2 x 100W COB Blinder Stage Light



- **Voltage:** AC 90V-240V Frequency: 50Hz - 60Hz
- **Source:** 100W LED lamp beads \* 2 (do single color or 2 in 1)
- **Color Temperature:** 3200-6500
- **Total Power:** 250W
- **Source life:** 50000-100000 hours
- **Dimming Frequency:** 1000Hz
- **Drive current:** 700mA
- **Strobe:** 1-10 times/second
- **Lens Angle:** 60 °
- **Type:** DMX512, self-propelled, master-slave
- **Control channel:** 8CH

## DM-COB100

### 130W Cold and Warm White COB Par Stage Light



- **Voltage:** AC100V-220V/50-60HZ
- **Power:** 130W
- **Color Emitting:** Cold White/Warm White
- **Light Time:** 100000 hours
- **Color Temperature:** 3200-6500K
- **Beam Angle:** 45 Degrees
- **Range:** 20 Meters
- **Dimmer:** 0-100% Dimming
- **Control Mode:** Standard DMX512, Automatic, and Master/Slave Mode
- **DMX Channel:** 6CH
- **Waterproof rating:** IP65

## DM-COB100P

### 100W Warm and White Color Par COB Stage Light



- **Power Supply:** AC100-240V, 50-60Hz
- **Power Consumption:** 100W
- **Light Source:** 1 Pcs x 100W WARM WHITE COB LED
- **Lamp Life:** 6-10 Thousand Hrs
- **Color:** Warm White + White
- **Control Mode:** DMX512, Master/Slave, Auto, Sound Active
- **Control Channels:** 3CHS/6CHS
- **Housing Material:** Die-Casting Aluminum

## DM-COB200

### 200W 60° Auto Zoom High Brightness COB Stage Light



- **Input Voltage:** AC90-240V 50/60Hz
- **Power:** 200W
- **Lighting Source:** 200W High-brightness COB LED
- **Channel Mode:** 2/3/4/5CH, Suitable for Different Places
- **Dimming speed:** 4 Kinds of Dimming Speed
- **Control mode:** DMX512, Master/Slave, Auto-un
- **Zoom:** Auto Zoom From 8-60 Degrees



# DMInteract® **WIRELESS PAR LIGHT**

High-Precision Wireless Par Lights—Illuminate  
Your Stage with Power and Focus



## DM-WBP130

### 130W 12Pcs 5in1 Wireless DMX Battery Par Stage Light



- **Voltage:** AC110V-250, 50-60 Hz
- **Power Consumption:** 130W
- **Source:** 12 pcs 10W/15W 5W High Brightness 5-in-1 LEDs
- **Lamp Life:** 6-10 Thousand Hrs
- **LED Angel:** 25° (± 5) Degree
- **Color:** 16.7 Million Kinds of Color Change
- **Control Channels:** 5/9 chs
- **Mode:** DMX512, Master/Slave, Auto, Sound
- **Operation Menu:** 4-Digit Digital LED Display
- **Automatic Model (by function button):** Color Change, Color Strobe, Color Dimmer, Color Gradual Change/Color Jump Change

## DM-COB100P

### 100W Warm and White Color Par COB Stage Light



- **Voltage:** AC110V-250, 50-60 Hz
- **Power Consumption:** 100W
- **Source:** 9 pcs 10W/15W High Brightness 6-in-1 LEDs
- **Lamp Life:** 6-10 Thousand Hrs
- **LED Angel:** 25° (± 5) Degree
- **Color:** 16.7 Million Kinds of Color Change
- **Control Channels:** 5/9 chs
- **Mode:** DMX512, Master/Slave, Auto, Sound
- **Operation Menu:** 4-Digit Digital LED Display
- **Automatic Model (by function button):** Color Change, Color Strobe, Color Dimmer, Color Gradual Change/Color Jump Change



# DMInteract<sup>®</sup> **LED PAR LIGHTS**

High-Precision LED Par Lights—Illuminate Your  
Stage with Power and Focus

## DM-PL180

### 180W Indoor 54Pcs RGB LED Par Stage Light



- **Lamp:** 54 PCS 3W LEDs
- **Power Consumption:** 180W
- **Lifespan:** 50000 hours
- **Emitting Color:** RGB 3 in 1
- **Beam Angle:** 25°
- **Strobe:** 1-18 times/sec high-speed strobe effect
- **Mechanical Dimming System:** 0-100% smooth linear dimming
- **Housing:** Aluminum
- **Protection Grade:** IP33
- **Control Signal:** DMX 512, master-slave, voice, auto
- **Control Channel:** 4/8CH

## DM-PL200

### 200W WaterProof 54Pcs LED Par Stage Light



- **Input Voltage:** 220V 50-60Hz
- **Output Voltage:** 28V
- **Power:** 200W
- **Color Mode:** (R12, G14, B14, W14)
- **Beam Angle:** 25° /38° /60° (Optional)
- **Control:** Standard DMX512 Signal
- **Channel:** 8CH
- **Waterproof:** IP67

## DM-PL200WX

### 80/200W Indoor 54Pcs LED Par Stage Light



- **Input Voltage:** AC90V-245V 50-60Hz
- **Power:** 80w-200w
- **Source:** 54 pcs x 3W High-brightness LED
- **Color Mode:** (R12, G19, B18, W6/R14, G14, B14, W112)
- **LED Angle:** 15°, 25°, 30°, 45° (Optional)
- **Channel:** 8CH
- **Control Mode:** DMX512, master-slave, auto, sound



## DM-PL1810

### 200W Indoor 18pcs 4 in1 RGBW LED Par Stage Light



- **Voltage:** 90V-240V AC, 50/60Hz
- **Power Consumption:** 200W
- **LED Source:** 18 pcs 10W RGBW 4-in-1 LED
- **LED lifespan:** 100000 hours
- **Control:** Master-Slave/Auto/Sound/DMX
- **DMX Channel:** 8CH
- **Case:** Silver or Black Aluminum House
- **Life:** 100,000 Hrs

## DM-PL250

### 250W Waterproof 4-in-1 18 piece LED Par Stage Light



- **Voltage:** 100-240V, 50/60Hz
- **Light source:** 18 x 10W LEDs 4 in 1
- **Power:** 250W
- **Beam angle:** 25°
- **Display:** 4 Push-button Menu with LED Display
- **Channel:** 8 Channel
- **Keywords:** Waterproof LED Par
- **Control Mode:** DMX512, Auto, Master/Slave



# DMInteract® **EFFECTS AND LASER LIGHTS**

High-Precision effect & Laser Lights–  
Illuminate Your Stage with Power and Focus

## DM-EL5W

### 5W Full Color Auto Laser Beam Stage Light



- **Voltage:** 110V-220V-250V, 50-60 Hz
- **Power:** 5W
- **Scanner:** 40 Kps Bragon Tiger High-speed optical, big angle scanning (0°-30°) Optional 30K
- **Laser:**
  - Green: 500mW 532nm, TE-cooled
  - Red: 500mW 638nm, TE-cooled
  - Blue: 2000mW 445nm
- **Control Mode:** Sound Active, Auto-Beam, auto-animation, DMX, Master/Slave, PC
- **Control DMX Channel:** 12CH.

## DM-EL2W

### 2W Full Color Auto Laser Beam Stage Light



- **Voltage:** 110V-220V-250V, 50-60 Hz
- **Power:** 2W
- **Scanner:** 40 Kps Bragon Tiger High-speed optical, big angle scanning (0°-30°) Optional 30K
- **Laser:**
  - Green: 500mW 532nm, TE-cooled
  - Red: 500mW 638nm, TE-cooled
  - Blue: 2000mW 445nm
- **Control Mode:** Sound Active, Auto-Beam, auto-animation, DMX, Master/Slave, PC
- **Control DMX Channel:** 12CH.

## DM-EL2W

### 3W Full Color Auto Laser Beam Stage Light



- **Voltage:** 110V-220V-250V, 50-60 Hz
- **Power:** 3W
- **Scanner:** 40 Kps Bragon Tiger High-speed optical, big angle scanning (0°-30°) Optional 30K
- **Control Mode:** Sound Active, Auto-Beam, auto-animation, DMX, Master/Slave, PC
- **Control DMX Channel:** 12CH.
- **PC Control:** Compatible ILDA Laser show software with ILDA interface uses electronic switches to convert full
- **Signal:** ILDA
- **Safe Capacity:** Design According to Security

## DM-EL10W

### 10W Full Color Auto Laser Beam Stage Light



- **Voltage:** 110V-220V-250V, 50-60 Hz
- **Power:** 50W
- **Scanner:** 40 Kps Bragon Tiger High-speed optical, big angle scanning (0°-30°) Optional 30K
- **Laser:**
  - Green: 500mW 532nm, TE-cooled
  - Red: 500mW 638nm, TE-cooled
  - Blue: 2000mW 445nm
- **Control Mode:** Sound Active, Auto-Beam, auto-animation, DMX, Master/Slave, PC
- **Control DMX Channel:** 12CH.

## DM-SL300W

### 300W Spider Laser Beam Stage Light



- **Voltage:** AC 90-240V, 50-60 Hz
- **Power:** 300W
- **Laser:** Red 400mw, Green 80mw, Blue 800mw
- **Channel:** 12/43 DMX Channels
- **XY axis Angle:** Pan 540, Tilt 120
- **Strobe:** High-speed electronic adjustment strobe/random strobe, 1-25 t/s
- **Operation mode:** Auto, Controller model, Master/slave.
- **Other facilities:** Variety of Built-in Programs, Cool Acoustic effect, suitable for bar, KTV, entertainment such as weddings
- **Outer shell:** Engineering Plastic, Aluminum Alloy

## DM-6ERL

### 180W 6 Eyes Single Red Laser Beam Stage Light



- **Voltage:** AC 100-240V 50/60HZ
- **Power:** 180W
- **Laser Power:** 6 pcs x Red 500 mw/638 nm
- **Color Temperature:** 2600 K
- **Tilt:** 270°
- **Control Mode:** DMX 512, Master-slave, Sound, Auto
- **DMX Channel:** 11CH/23CH



## DM-150MBL

### 150W 8Pcs 4in1 Moving Bar Laser Beam Stage Light



- **Voltage:** AC100-240V 50-60Hz
- **LED:**
  - 8 PCS × 10W White CREE LED
  - 8PCS×10W RGBW (4IN1) CREE LED
- **Power:** 150W
- **Mode:** Auto, Sound, DMX, Program
- **DMX mode:** 12CH
- **LCD:** Blue
- **Power Failure Memory:** Set slave ID





# DMInteract® **FOLLOW LIGHTS**

High-Precision Follow Lights—Illuminate Your  
Stage with Power and Focus

## DM-350FSL

### 350W 4 Colors Wheel With Lumens LED Follow Stage Spotlight



- **Support Voltage:** AC220V-240V 50- 60Hz
- **Bulb Specifications:** LED 350W
- **Colors:** Color Wheel 4 Kinds of Color + White light, Gobo can be determined
- **Control Signal:** Mixed signals, control knob
- **Control Mode:** Stand-alone Mode
- **Optical System:** US LUMENS LED
- **Cooling System:** High-strength Air-cooled
- **Aperture Effect:** Aperture Size is Adjustable
- **Stroboscopic:** Stroboscopic 1-7 times/SEC
- **Color Temperature Correction:** Normal 5600k, Max 6000k, Min 3200K
- **Speed of light distance:** 30-60m
- **Speed of light Angle:** 23 degrees





SPECIAL OFFER

# ORDER NOW



[www.dminteract.com](http://www.dminteract.com)



[www.dubaimachines.com](http://www.dubaimachines.com)



**DEALER ADDRESS:**

Showroom G-02, IT Plaza, Dubai Silicon Oasis, Dubai, United Arab Emirates



**CANADA OFFICE:**

DMInteract Inc 801 Dundas Street East, Unit #D6, Mississauga, Ontario, L4Y 4G9



**CONTACT NUMBER:**

+971-4-3360300 - (Dubai Office)

437-880-7712 - (Mississauga Office)



**EMAIL ADDRESS:**

[info@dminteract.com](mailto:info@dminteract.com)