

VGA Cables

Product features

- Made with high-quality material.
- Ferrite Cores.
- Double shielded (foil and braided).
- Quality HD-15 connectors.
- Molded connectors.
- Easy to use screws caps.
- 3 Analog & 8 signal connectors.
- Available in various lengths.
- Manufactured to meet or exceed UL VW-1 standards.



Model ID	Wavelength	Connections	Conductor	Insulator	Shell
ANVGA2	2m	15-Pin Male to Male with Audio	3x26AWG+7x24 AWG OFC	Foam Skin PE/PBT, UL 94V-0 Rated	PVC Black with ferrite beads
ANVGA3	3m	15-Pin Male to Male with Audio	3x26AWG+7x24 AWG OFC	Foam Skin PE/PBT, UL 94V-0 Rated	PVC Black with ferrite beads
ANVGA6	6m	15-Pin Male to Male with Audio	3x26AWG+7x24 AWG OFC	Foam Skin PE/PBT, UL 94V-0 Rated	PVC Black with ferrite beads
ANVGA10	10m	15-Pin Male to Male with Audio	3x26AWG+7x24 AWG OFC	Foam Skin PE/PBT, UL 94V-0 Rated	PVC Black with ferrite beads
ANVGA15	15m	15-Pin Male to Male with Audio	3x26AWG+7x24 AWG OFC	Foam Skin PE/PBT, UL 94V-0 Rated	PVC Black with ferrite beads
ANVGA 20	20m	15-Pin Male to Male with Audio	3x26AWG+7x24 AWG OFC	Foam Skin PE/PBT, UL 94V-0 Rated	PVC Black with ferrite beads

Model ID	Wavelength	Connections	Conductor	Insulator	Shell
ANVGA30	30m	15-Pin Male to Male with Audio	3x26AWG+7x24 AWG OFC	Foam Skin PE/PBT, UL 94V-0 Rated	PVC Black with ferrite beads
ANVGA5-OP	5m	15-Pin Male to open	3x26AWG+7x24 AWG OFC	Foam Skin PE/PBT, UL 94V-0 Rated	PVC Black with ferrite beads
ANVGA10-OP	10m	15-Pin Male to open	3x26AWG+7x24 AWG OFC	Foam Skin PE/PBT, UL 94V-0 Rated	PVC Black with ferrite beads
ANVGA15-OP	15m	15-Pin Male to open	3x26AWG+7x24 AWG OFC	Foam Skin PE/PBT, UL 94V-0 Rated	PVC Black with ferrite beads
ANVGA20-OP	20m	15-Pin Male to open	3x26AWG+7x24 AWG OFC	Foam Skin PE/PBT, UL 94V-0 Rated	PVC Black with ferrite beads
ANVGA5w/o	5m	15-Pin Male to Male without Audio	3x26AWG+7x24 AWG OFC	Foam Skin PE/PBT, UL 94V-0 Rated	PVC Black with ferrite beads
ANVGA10w/o	10m	15-Pin Male to Male without Audio	3x26AWG+7x24 AWG OFC	Foam Skin PE/PBT, UL 94V-0 Rated	PVC Black with ferrite beads
ANVGA15w/o	15m	15-Pin Male to Male without Audio	3x26AWG+7x24 AWG OFC	Foam Skin PE/PBT, UL 94V-0 Rated	PVC Black with ferrite beads
ANVGA20w/o	20m	15-Pin Male to Male without Audio	3x26AWG+7x24 AWG OFC	Foam Skin PE/PBT, UL 94V-0 Rated	PVC Black with ferrite beads

