

Key Features

Seamless viewing experience | Loaded with connectivity | Ultimate color accuracy and screen uniformity | Professional color processing capability | Versatile color adjustability



Product **Description**

The ViewSonic® VP2468 is a 24" (23.8" viewable) Full HD monitor that delivers unmatched color accuracy crucial for professional applications. With an edge-to-edge SuperClear Pp panel and one of the world's thinnest bezels, the VP2468 provides a sleek and frameless viewing experience ideal for multi-monitor setups. For simple, single-cable daisy chaining of multiple monitors, the VP2468 is equipped with future-proof DisplayPort technology, in addition to HDMI ports. What's more, with advanced ergonomic tilt, swivel, pivot, and height adjust features, this monitor provides a comfortable viewing experience and vivid images no matter your vantage point. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E<2 value for superior color accuracy. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. Add to that 6-axis color adjustment functionality, and this monitor provides the ultimate color processing capability for professional applications. Hardware calibration is available with the optional ViewSonic Colorbration Kit, which allows you to quickly and easily calibrate the monitor for photography, graphic design, content creation, and other color-critical applications.



- 1. VESA Compatible Wall Mount 100 x 100 mm
- 2. Menu Controls
- 3. AC In



- 4. HDMI x2 5. DisplayPort
- 7. USB Type B
- 6. Headphone
- 01 06 0 07 03 08 04 0 09 05 -0 10
 - 8. USB 3.0 x4
 - 9. DisplayPort Out
 - 10. Mini DisplayPort









Display:		Ergonomics:	
Display Size (in.):	24	Height Adjust (mm):	130
Viewable Area (in.):	23.8	Swivel:	120°
Туре:	IPS	Pivot:	900
Resolution:	1920 x 1080	Tilt (Forward/Back):	5°/21°
Static Contrast Ratio:	1000:1	Weight (imperial):	
Dynamic Contrast Ratio:	20M:1	Net (lbs):	12.5
Light Source:	LED	Net Without Stand (lbs):	7.0
Brightness:	250 cd/m2	Gross (lbs):	17.1
Colors:	16.7M	Weight (metric):	
Response Time (Typical GTG):	5ms	Net (kg):	5.7
Viewing Angles:	178º horizontal, 178º vertical	Net Without Stand (kg):	3.2
Backlight Life (Hours):	30,000	Gross (kg):	7.75
Panel Surface:	Anti-glare, hard-coating (3H)	Dimensions (imperial) (WxHxD):	
Compatibility:		Packaging (in.):	25.6 x 16.2 x 10.6
PC Resolution (max):	Up to 1920x1080 non-interlaced	Physical (in.):	21.2 x 20.5 x 8.5
Mac® Resolution (max):	Up to 1920x1080	Physical Without Stand (in.):	21.2 x 12.2 x 1.9
Connector:		Dimensions (metric) (WxHxD):	
USB 3.0 Type A(4), USB 3.0 Type B(1), 3.5mm Audio Out(1), HDMI 1.4(2), Display Port(1), Display Port Out(1), Mini Display Port(1), Power in(3-pin plug (CEE22))		Packaging (mm):	650 x 412 x 270
		Physical (mm):	538.7 x 519.5 x 215
Power:		Physical Without Stand (mm):	538.7 x 310.5 x 48.1
Eco Mode (Conserve):	17W	General:	
Eco Mode (optimized):	19W	Regulations: CB, CE, WEEE, RoHS, ErP, REACH, UL, FCC-B, Mexico CoC, EPEAT GOLD, ENERGY STAR, Mexico Energy	
Consumption (typical):	22W	PACKAGE CONTENTS: VP2468 monitor, Power cable, Mini DisplayPort to	
Voltage:	AC 100-240V (universal), 50-60Hz	DisplayPort cable, USB 3.0 Cable, Quick Start Guide, ViewSonic Wizard CD	
Controls:		Recycle/Disposal: Please dispose of federal laws.	in accordance with local, state or
Physical Controls:	Power, 1, 2, 3, 4, 5	Warranty: Three-year limited warranty on parts, labor and backlight	
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu (See user guide for complete OSD	UPC: 766907844818	
		Accessories:	
	functionality)		
Operating Conditions:		Awards:	
Operating Conditions: Temperature:	32-104° F (0-40° C)	Awards:	
_	32-104° F (0-40° C) 20-90%	Awards:	
Temperature:		Awards:	
Temperature: Humidity (non-condensing):		Awards:	
Temperature: Humidity (non-condensing): Mount:	20-90%	Awards:	
Temperature: Humidity (non-condensing): Mount: VESA Compatible:	20-90%	Awards:	
Temperature: Humidity (non-condensing): Mount: VESA Compatible: Video Signal:	20-90% 100 x 100 mm	Awards:	
Temperature: Humidity (non-condensing): Mount: VESA Compatible: Video Signal: Frequency Horizontal:	20-90% 100 x 100 mm 15~90kHz	Awards:	

Copyright © ViewSonic Corporation 2000-2017. All rights reserved. (06/19/2017 09:34 PM PST)