

Combining speed and reliability for maximum productivity



EPSON DFX-9000

With speeds up to 1550 cps and an MTBF rating of 20,000 power-on hours (POH), the Epson DFX-9000 offers the power and durability to tackle the most demanding print tasks. Day after day, you can count on it to efficiently

process everything from reports and 10-part forms to shipping documents or mailing labels.

A robust, dependable workhorse, this 9-pin, wide-format printer boasts a 400-million-character print head life and 15-million-character ribbon cartridge, which minimizes production costs and reduces the need for frequent user intervention. Its advanced paper handling capabilities make it the perfect solution for a wide variety of applications, including critical spreadsheets, checks, invoices, bar codes and more.

Featuring two standard paper paths, the DFX-9000 easily switches between multiple applications. Its intelligent paper sensor detects the paper width and thickness, adjusting automatically for optimum performance and high-quality results. It even features an automatic jam sensor to prevent wasting forms in the unlikely event of a paper jam.

With Parallel, Serial, and USB interfaces standard, plus a type-B slot for optional connectivity, the DFX-9000 easily attaches to new or legacy systems in standalone or networked environments. And, its convenient LCD display and intuitive menu selections mean setup has never been easier. Plus, it's all backed by Epson's one-year on-site warranty for superior service and support.

Key Features

- **Blaze through critical reports with ultra-fast print speeds**
 - Prints multipart forms, labels, and more at speeds up to 1550 cps
- **Tackle the most demanding print tasks**
 - Durable 9-pin performer offers an MTBF rating of 20,000 POH at 25% duty cycle
- **Get dependable print performance, day after day**
 - Boasts a 400-million-character print head life
- **Minimize your application costs**
 - 15-million-character ribbon cartridge ensures low cost printing and reduces the need for frequent user intervention
- **Simplify the integration process**
 - Convenient LCD display allows for easy printer configuration and menu navigation
- **Meet all your printing needs with flexible forms handling capabilities**
 - Prints 136-column, wide-format reports, plus forms up to 10 parts thick
 - Front and rear paper paths
 - Platen gap adjusts automatically, according to the paper thickness
 - Auto jam sensor eliminates wasting forms
- **Use with new or legacy systems**
 - Enhanced connectivity supports standard Parallel, Serial, and USB interfaces
 - Accommodates optional internal Type B interface boards for easy networking
- **Enjoy the added confidence of superior Epson service and support**
 - Includes a one-year on-site limited warranty in the U.S. and Canada



EPSON®

IMPACT PRINTER

DFX-9000

Printing Method

9-pin impact dot matrix

Print Direction

Text Mode: Bidirectional
Graphics Mode: Unidirectional (bidirectional via software)

Print Speed

High Speed Draft	1550 cps (10 cpi)
Draft	1320 cps (10 cpi)
Near Letter Quality	330 cps (10 cpi)

Character Sets

11 character tables, 13 international character sets

Resident Fonts (cpi)

Epson Super Draft	10
Epson Draft	10, 12
Epson NLQ Roman	10, 12, proportional
Epson NLQ San Serif	10, 12, proportional
Bar Code Fonts	EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code-39, Code-128, POSTNET

Printable Columns

136 columns (10 cpi)

Formatting

Tabs	10 sets vertical tabs, 32 horizontal tabs
Line spacing	1/6", 1/8" or programmable (min 1/216")
Perforation skip	Skip over perforation programmable in lines

Paper Feed Speed

Approximately 26.5 ms/line at 1/6" line spacing; 15 inches per second (continuous feed)

Paper Paths

Push tractor	Front or rear in, top out
Pull tractor	Front or rear in, top out

Paper Feed Methods

Dual push tractors/paper paths: automatic back-out and loading; automatic paper thickness adjustment; automatic paper width detection; microadjustment for top-of-form and tear-off mode; adjustable tractor feed; perforation cutter (optional); pull tractor (optional)

Input Buffer

128KB or 0KB, user selectable

Software Drivers*

Windows 95, 98, 98SE, 2000, XP, Me and NT 3.51/4.0

Standard Interfaces

Bidirectional IEEE 1284 Parallel
USB 1.1, RS-232C Serial
Type B slot for optional interface boards

Optional Interfaces

10/100 Base T Ethernet, RS-232 Serial, Coax, Twinax

Printer Languages

ESC/P® IBM PPDS

Paper Handling

Multi-part Forms	
Front	1 original + 9 copies
Rear	1 original + 6 copies
Continuous Feed	3.0" to 16.5"
Labels	2.5" x .94" (min)
Page length	3.5" minimum for forms with labels

Sound Level

58 dB (A)

Power Requirements

50 - 60Hz ± .5Hz; 200 watts; 100-240 volt
Energy Star compliant

Physical Dimensions

Height	14.3"
Width	27.6"
Depth	14.9"
Weight	75 lb

Reliability

MTBF	20,000 POH (25% duty cycle)
Print head life	400 million characters
Ribbon life	15 million characters (draft, 10 cpi, 14 dots/character)

Warranty

One-year on-site limited warranty in the U.S. and Canada

Support-The Epson Connection™

Automated Technical Support	(800) 922-8911
Pre-Sales Support U.S. & Canada	(800) 463-7766
Internet Website	www.epson.com

* Additional software drivers available in your Windows operating system, or at www.epson.com.
** Field upgrade of Flash ROM to be done by Epson authorized service centers

Epson DFX-9000

C11C605001	Epson DFX-9000 printer
S015384	Epson DFX-9000 ribbon cartridge
C12C800381	Pull tractor unit
C815071	Perforation cutter
8502	Printer stand
C823051	Serial interface
C823071	32KB Serial interface
C823121	LocalTalk interface
C823141	Coax interface
C823151	Twinax interface
C823452	Bidirectional Parallel interface
C12C823912	Multiprotocol 10/100 Base-TX Ethernet Print Server



Epson America, Inc.
3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.
3771 Victoria Park Avenue, Toronto, Ontario M1W 3Z5

Specifications and terms are subject to change without notice. Epson and Epson ESC/P are registered trademarks and Exceed Your Vision is a trademark of Seiko Epson Corporation. Epson Connection is a service mark of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. © Copyright 2005 Epson America, Inc. CPD-19846 5/05

