

# AC Digital Clamp Meters

## KT 200



- Small and handy clamp meter
- IEC 61010-1 Safety Standard CAT III 300V, CAT II 600V
- 400A AC Clamp meter
- DMM function ACV, DCV,  $\Omega$ , Continuity Buzzer.

CE

$\phi 30$

MAX  
400A

AC **A**

DC  
AC **V**

$\Omega$

•••••

DATA  
HOLD

AUTO POWER  
SAVE

AC A	40.00/400.0A $\pm 2.0\% \text{rdg} \pm 6 \text{dgt} (50/60\text{Hz})$
AC V	400.0/600V(Auto-ranging) $\pm 2.0\% \text{rdg} \pm 5 \text{dgt} (50/60\text{Hz})$
DC V	400.0/600V(Auto-ranging) $\pm 1.5\% \text{rdg} \pm 5 \text{dgt}$
$\Omega$	400.0/4000 $\Omega$ (Auto-ranging) $\pm 2.0\% \text{rdg} \pm 5 \text{dgt}$
Continuity buzzer	buzzer sounds below $50 \pm 35\Omega$
Conductor size	$\phi 30\text{mm}$ max.
Applicable standards	IEC 61010-1 CAT III 300V(ACA), CAT II 600V Pollution degree 2 IEC 61010-2-032, IEC 61326-1
Power source	R03(1.5V)(AAA) $\times 2$ *Continuous measuring time: Approx. 200hours (Auto power save: approx. 10 minutes)
Dimensions	184(L) $\times$ 68.6(W) $\times$ 38.5(D)mm
Weight	Approx. 190g(including batteries)
Included Accessories	7066A (Test leads) R03 (AAA) $\times 2$ , Instruction Manual
Optional Accessories	9105 (Carrying case)